

INDUSTRIAL COMPONENT DATA

XV-102-H4-35TQRL-10 171159 Y7-171159 EATON ELECTRIC

Control tableau, 24 VDC, human-machine interface, 3, 5 i..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-102-H4-35TQRL-10



Manufacturer	EATON - MOELLER
MPN / Reference	XV-102-H4-35TQRL-10
Catalog number	Y7-171159
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-8CDCC3B2B6
Generated	2026-08-05

Product Overview

Control tableau, 24 VDC, human-machine interface, 3, 5 inch, Ethernet, RS485, CE50C

XV-102-H4-35TQRL-10

User interface, XV-102, Product range: XV100 3.5z, Function: HMI, Common features of the model series: Ethernet interface, USB device, Slot for SD card, UL508, cUL approvals, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colors: 64 k Colors, Resolution: QVGA, 320 x 240 Pixel, Portrait format: yes, Screen diagonal: 3.5 Inch, Insulating enclosure and front plate, Operating system: Windows CE 5.0 (license incl.), PLC-license: no PLC function possible, License certificates for onboard interfaces: Can be expanded as required, see Accessories -> License product certificates , built-in interfaces: 1 x Ethernet 10/100 Mbps, 1 x RS485, Front type: Standard front with standard membrane (fully enclosed), Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 139807, Pluggable communication cards (optional): no, Heat dissipation: 5 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > HMI Touch Terminals**

Additional Product Information

General specifications

Product Name Eaton XV-102 Touch panel Catalog Number 171159 Model Code XV-102-H4-35TQRL-10 EAN

7640130097964 Product Length/Depth 136 mm Product Height 30 mm Product Width 100 mm Product Weight 0.245 kg

Certifications IEC/EN 61000-6-4

UL 60950-01

CUL508

CE

EN 50178

IEC/EN 61131-2

UL 60950

UL report applies to both US and Canada

Certified by UL for use in Canada

UL Recognized

IEC/EN 61000-6-2

UL Category Control No.: NWGQ2

EN 60950

UL File No.: E208621

CSA Class No.: NWGQ8

CSA-C22.2 No. 60950-1

EAC Features & Functions

Enclosure material Plastic Features Slot for SD card

USB device

UL508, cUL approvals

Ethernet interface

Portrait format Fitted with: SW interfaces

Numeric keyboard

1 x Ethernet 10/100 Mbps (built-in interfaces)

Message indication

Message system (incl. buffer and confirmation)

Recipes

1 x RS485 (built-in interface)

Printer output

Alpha numeric keyboard

Color display Functions HMI

Additional software components, loadable

Process value representation (output) possible

Process default value (input) possible General

Battery runtime Back-up of real-time clock: CR 2032 (190 mA/h), zero maintenance (soldered) Conditions of acceptability

UL/CSA

The provided Ethernet Connection is only allowed to connect to inhouse networks.

The investigated Pollution Degree is: 2

The following end-product enclosures are required: Fire

The unit must be supplied via a SELV source. Degree of protection IP20, rear

IP65 Degree of protection (front side) IP65

NEMA 4X Fu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-102-H4-35TQRL-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.