

INDUSTRIAL COMPONENT DATA

XV-303-10-B00-A00-1B 179659 Y7-179659 EATON ELECTRIC

XV-303-10-B00-A00-1B Control panel, 24 V DC, 10 Inches ..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-10-B00-A00-1B



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-10-B00-A00-1B
Catalog number	Y7-179659
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-4A7ECF2208
Generated	2026-08-06

Product Overview

XV-303-10-B00-A00-1B Control panel, 24 V DC, 10 Inches PCT-Display, 1024x600 pixels, 1xEthernet, 1xRS232, 1xRS485, 1xCAN, 1xSD card slot, PLC function can be fitted by user

XV-303-10-B00-A00-1B

Multi-Touch Display, XV-303, Product range: XV300 10.1z, Function: HMI-PLC (PLC retrofitted by user), Control panel, Common features of the model series: Ethernet interface, CAN, USB device, USB Host, RS232, RS485, Slot for SD card, Operating System Windows Embedded Compact 7 pro, Integrated Runtime visualization software license, Display - Type: Color display, TFT, anti-glare, Touch-technology: Capacitive multi-touch technology (PCT), Number of colors: 16777216 (Color depth 24 bit), Resolution: WSVGA, 1024 x 600 Pixel, Portrait format: yes, Screen diagonal: 10.1, widescreen Inch, Plastic enclosure and glass panel in plastic frame , Operating system: Windows Embedded Compact 7 Pro, PLC-license: Can be fitted by user with article no. 181585 LIC-PLC-A, License certificates for onboard interfaces: Not required, built-in interfaces: 1 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen®/easyNet, Front type: Anti-glare tempered glass in plastic bezel, Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 181638, Pluggable communication cards (optional): no, Touch sensor: Multi-touch touch pan...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > HMI Touch Terminals**

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 179659 Model Code XV-303-10-B00-A00-1B EAN

7640130098541 Product Length/Depth 269 mm Product Height 58 mm Product Width 174 mm Product Weight 1.165 kg

Certifications IEC/EN 61131-2

UL

UL File No.: E205091

DNV GL

UL 61010-2-201

CE

Certified by UL for use in Canada

CUL

EMC according to 2014/30/EU

EN 50178 Features & Functions

Enclosure material Insulated material Features Fanless CPU and system cooling, natural convection-based passive cooling

Slot for SD card

CAN

USB device

RS232

Target and web visualization

RS485

Integrated Runtime visualization software license

Portrait format

Ethernet interface

USB Host

Operating System Windows Embedded Compact 7 pro Fitted with: 1 x USB device (built-in interface)

Color display

1 x RS485 (built-in interface)

Message system (incl. buffer and confirmation)

Recipes

SW interfaces

1 x Ethernet 10/100 Mbps (built-in interfaces)

Message indication

1 x CANopen®/easyNet (built-in interfaces)

1 x USB host 2.0 (built-in interface)

1 x RS232 (built-in interface)

Printer output Functions Process value representation (output) possible

Additional software components, loadable

Process default value (input) possible General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection NEMA 4X

IP20, rear (according to EN 60529-1)

NEMA 12 Degree of protection (front side) NEMA 12

IP65 Fuse type Built-in fuse (not accessible) Lifespan 50,000 h (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-10-B00-A00-1B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.