

INDUSTRIAL COMPONENT DATA

XV-303-10-C00-A00-1C 179662 Y7-179662 EATON ELECTRIC

XV-303-10-C00-A00-1C Control panel with PLC, 24 V DC, 1..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-10-C00-A00-1C



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-10-C00-A00-1C
Catalog number	Y7-179662
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-234DB088BF
Generated	2026-08-06

Product Overview

XV-303-10-C00-A00-1C Control panel with PLC, 24 V DC, 10 Inches PCT-Display, 1024x600 pixels, 2xEthernet, 1xRS232, 1xRS485, 1xCAN, 1xSD card slot

XV-303-10-C00-A00-1C

Multi-Touch Display with PLC, XV-303, Product range: XV300 10.1z, Function: HMI-PLC (PLC integrated), Control panel with PLC and 2nd Ethernet port, Common features of the model series: Ethernet interface, CAN, USB device, USB Host, RS232, RS485, Slot for SD card, Operating System Windows Embedded Compact 7 pro, Integrated Runtime visualization software license, Display - Type: Color display, TFT, anti-glare, Touch-technology: Capacitive multi-touch technology (PCT), Number of colors: 16777216 (Color depth 24 bit), Resolution: WSVGA, 1024 x 600 Pixel, Portrait format: yes, Screen diagonal: 10.1, widescreen Inch, Plastic enclosure and glass panel in plastic frame, Operating system: Windows Embedded Compact 7 Pro, PLC-license: PLC license inclusive, License certificates for onboard interfaces: Not required, built-in interfaces: 2 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x CANopen®/easyNet, 1 x USB host 2.0, 1 x USB device, Front type: Anti-glare tempered glass in plastic bezel, Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 181638, Pluggable communication cards (optional): no, Touch sensor: Multi-touch touch panel, Heat dissipation: 18 W, D...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > HMI Touch Terminals

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 179662 Model Code XV-303-10-C00-A00-1C EAN

7640130098749 Product Length/Depth 269 mm Product Height 58 mm Product Width 174 mm Product Weight 1.165 kg
Certifications IEC/EN 61131-2
UL 61010-2-201
EMC according to 2014/30/EU
EN 50178
CE
DNV GL
Certified by UL for use in Canada
CUL
UL
UL File No.: E205091 Features & Functions
Enclosure material Insulated material Features Portrait format
Slot for SD card
USB device
CAN
RS485
Ethernet interface
Target and web visualization
Operating System Windows Embedded Compact 7 pro
Fanless CPU and system cooling, natural convection-based passive cooling
RS232
USB Host
Integrated Runtime visualization software license Fitted with: 1 x RS485 (built-in interface)
Recipes
1 x USB host 2.0 (built-in interface)
SW interfaces
Printer output
1 x USB device (built-in interface)
Message indication
1 x CANopen®/easyNet (built-in interfaces)
2 x Ethernet 10/100 Mbps (built-in interface)
1 x RS232 (built-in interface)
Message system (incl. buffer and confirmation)
Color display Functions Process value representation (output) possible
Process default value (input) possible
Additional software components, loadable General
Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection IP20, rear (according to EN 60529-1)
NEMA 12
NEMA 4X Degree of protection (front side) NEMA 12
IP65 Fuse type Built-in fuse (not accessible) Lifespan 50,000 h (S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-10-C00-A00-1C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.