

INDUSTRIAL COMPONENT DATA

XV-303-10-C02-A00-1B 179664 Y7-179664 EATON ELECTRIC Control panel, 24VDC, 10.1-inch PCT display,1024x600 pi..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-10-C02-A00-1B



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-10-C02-A00-1B
Catalog number	Y7-179664
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-E25EC72305
Generated	2026-08-05

Product Overview

Control panel, 24VDC, 10.1-inch PCT display,1024x600 pixels,2xEthernet,1xRS232, 1xRS485, 1xCAN, 1xProfibus, 1xSD card slot, PLC function can be added

XV-303-10-C02-A00-1B

Eaton XV-303 User interface, 24VDC, 10.1-inch PCT display,1024x600 pixels,2xEthernet,1xRS232, 1xRS485, 1xCAN, 1xProfibus, 1xSD card slot, PLC function can be added

Multi-Touch Display, XV-303, Product range: XV300 10.1z, Function: HMI-PLC (PLC retrofitted by user), Control panel with PROFIBUS and 2nd Ethernet port, Common features of the model series: Ethernet interface, CAN, USB device, USB Host, RS232, RS485, Slot for SD card, Operating System Windows Embedded Compact 7 pro, Integrated Runtime visualization software license, Display - Type: Color display, TFT, anti-glare, Touch-technology: Capacitive multi-touch technology (PCT), Number of colors: 16777216 (Color depth 24 bit), Resolution: WSVGA, 1024 x 600 Pixel, Portrait format: yes, Screen diagonal: 10.1, widescreen Inch , Plastic enclosure and glass panel in plastic frame, Operating system: Windows Embedded Compact 7 Pro, PLC-license: Can be fitted by user with article no. 181585 LIC-PLC-A, License certificates for onboard interfaces: Not required, built-in interfaces: 2 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x CANopen@/easyNet, 1 x USB host 2.0, 1 x USB device, 1 x PROFIBUS/MPI, Front type: Anti-glare tempered glass in plastic bezel, Utilizati...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > HMI Touch Terminals**

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 179664 Model Code XV-303-10-C02-A00-1B EAN

7640130098756 Product Length/Depth 269 mm Product Height 58 mm Product Width 174 mm Product Weight 1.195 kg

Certifications EMC according to 2014/30/EU

DNV GL

EN 50178

UL File No.: E205091

CUL

IEC/EN 61131-2

CE

UL 61010-2-201

Certified by UL for use in Canada

UL Features & Functions

Enclosure material Insulated material Features Slot for SD card

Target and web visualization

Operating System Windows Embedded Compact 7 pro

USB device

RS485

Portrait format

CAN

Fanless CPU and system cooling, natural convection-based passive cooling

Ethernet interface

RS232

Integrated Runtime visualization software license

USB Host Fitted with: Message indication

Message system (incl. buffer and confirmation)

Recipes

Printer output

Color display

1 x USB device (built-in interface)

1 x PROFIBUS/MPI (built-in interface)

MPI interface

2 x Ethernet 10/100 Mbps (built-in interface)

1 x RS232 (built-in interface)

SW interfaces

1 x CANopen®/easyNet (built-in interfaces)

1 x USB host 2.0 (built-in interface)

1 x RS485 (built-in interface) Functions Additional software components, loadable

Process value representation (output) possible

Process default value (input) possible General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection NEMA 12

NEMA 4X

IP20, rear (according to EN 60529-1) Degree of protection (front side) IP65

NEMA 12 Fuse type...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-10-C02-A00-1B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.