

INDUSTRIAL COMPONENT DATA

XV-303-15-C00-A00-1D 191077 Y7-191077 EATON ELECTRIC

User interface, 24VDC, 15.6-inch PCT widescreen display..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-15-C00-A00-1D



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-15-C00-A00-1D
Catalog number	Y7-191077
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-FA76032B40
Generated	2026-08-05

Product Overview

User interface, 24VDC, 15.6-inch PCT widescreen display, 1366x768 pixels, 2xEthernet, 1xRS232, 1xRS485, 1xCAN, 1xSD card slot, VisualDesigner
XV-303-15-C00-A00-1D

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 191077 Model Code XV-303-15-C00-A00-1D EAN 7640130099166 Product Length/Depth 403.7 mm Product Height 76.6 mm Product Width 254.9 mm Product Weight 3.9 kg Certifications EN 50178

CUL

EMC according to 2014/30/EU

DNV GL

IEC/EN 61131-2 Features & Functions

Enclosure material Insulated material

Aluminum (die-cast, glass panel) Features USB device

RS485

USB Host

Target and web visualization

CAN

Integrated Runtime visualization software license

Slot for SD card

Fanless CPU and system cooling, natural convection-based passive cooling

Portrait format

Operating System Windows Embedded Compact 7 pro

Ethernet interface

RS232 Fitted with: 1 x RS232 (built-in interface)

Message indication

1 x USB device (built-in interface)

1 x RS485 (built-in interface)

Recipes

Printer output

SW interfaces

Message system (incl. buffer and confirmation)

1 x USB host 2.0 (built-in interface)

Color display

1 x CANopen®/easyNet (built-in interfaces)

2 x Ethernet 10/100 Mbps (built-in interface) Functions Process default value (input) possible

Process value representation (output) possible

Additional software components, loadable General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection IP20, rear (according to EN 60529-1)

NEMA 12

NEMA 4X Degree of protection (front side) NEMA 12

IP65 Fuse type Built-in fuse (not accessible) Lifespan 50,000 h (Service life of back-lighting) Model Pla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-15-C00-A00-1D with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.