

INDUSTRIAL COMPONENT DATA

XV-303-15-C02-A00-1B 191073 Y7-191073 EATON ELECTRIC

User interface, 24VDC,15.6-inch PCT widescreen display,..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-15-C02-A00-1B



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-15-C02-A00-1B
Catalog number	Y7-191073
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-D7D6F84E56
Generated	2026-08-06

Product Overview

User interface, 24VDC,15.6-inch PCT widescreen display,1366x768,2xEthernet,1xRS232,1xRS485,1xCAN,1xProfibus,1xSD card slot, PLC function can be added
XV-303-15-C02-A00-1B

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 191073 Model Code XV-303-15-C02-A00-1B EAN 7640130099128 Product Length/Depth 403.7 mm Product Height 76.6 mm Product Width 254.9 mm Product Weight 3.9 kg
Certifications DNV GL
EN 50178
CUL
EMC according to 2014/30/EU
IEC/EN 61131-2 Features & Functions
Enclosure material Aluminum (die-cast, glass panel)
Insulated material Features USB device
Slot for SD card
Target and web visualization
CAN

Portrait format
Ethernet interface
Operating System Windows Embedded Compact 7 pro
Fanless CPU and system cooling, natural convection-based passive cooling
RS485
Integrated Runtime visualization software license
USB Host
RS232 Fitted with: 1 x USB host 2.0 (built-in interface)
SW interfaces
1 x USB device (built-in interface)
Color display
Message system (incl. buffer and confirmation)
1 x RS485 (built-in interface)
Message indication
Recipes
1 x CANopen®/easyNet (built-in interfaces)
1 x RS232 (built-in interface)
Printer output
2 x Ethernet 10/100 Mbps (built-in interface)
1 x PROFIBUS/MPI (built-in interface)
MPI interface Functions Process value representation (output) possible
Process default value (input) possible
Additional software components, loadable General
Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection NEMA 4X
IP20, rear (according to EN 60529-1)
NEMA 12 Degree of protection (front side) NEMA 12
IP65 Fuse type Built-in fuse (not accessible) Lifespa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-15-C02-A00-1B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.