

INDUSTRIAL COMPONENT DATA

XV-303-15-C02-A00-1C 191074 Y7-191074 EATON ELECTRIC

User interface with PLC, 24VDC, 15.6-inch PCT widescreen..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-15-C02-A00-1C



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-15-C02-A00-1C
Catalog number	Y7-191074
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-9838C2F1D6
Generated	2026-08-06

Product Overview

User interface with PLC, 24VDC, 15.6-inch PCT widescreen display, 1366x768 pixels, 2xEthernet, 1xRS232, 1xRS485, 1xCAN, 1xProfibus, 1xSD card slot

XV-303-15-C02-A00-1C

Multi-Touch Display with PLC, XV-303, Product range: XV300 15.6z, Function: HMI-PLC (PLC integrated), Control panel with PLC, PROFIBUS, and 2nd Ethernet port, Common features of the model series: Ethernet interface, CAN, USB device, USB Host, RS232, RS485, Slot for SD card, Operating System Windows Embedded Compact 7 pro, Integrated Runtime visualization software license, Display - Type: Color display, TFT, anti-glare, Touch-technology: Capacitive multi-touch technology (PCT), Number of colors: 16777216 (Color depth 24 bit), Resolution: WXGA, 1366 x 768 Pixel, Portrait format: yes, Screen diagonal: 15.6, widescreen Inch , Glass panel in aluminum bezel with die-cast aluminum enclosure and plastic enclosure, Operating system: Windows Embedded Compact 7 Pro, PLC-license: PLC license inclusive, License certificates for onboard interfaces: Not required, built-in interfaces: 2 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x CANopen®/easyNet, 1 x USB host 2.0, 1 x USB device, 1 x PROFIBUS/MPI, Front type: Non-reflective tempered glass in aluminum frame, Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 181638, Pluggable communication cards (optional):....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 191074 Model Code XV-303-15-C02-A00-1C EAN

7640130099135 Product Length/Depth 403.7 mm Product Height 76.6 mm Product Width 254.9 mm Product Weight 3.9 kg

Certifications CUL

EN 50178

IEC/EN 61131-2

EMC according to 2014/30/EU

DNV GL Features & Functions

Enclosure material Aluminum (die-cast, glass panel)

Insulated material Features Ethernet interface

CAN

RS485

Portrait format

USB device

RS232

USB Host

Operating System Windows Embedded Compact 7 pro

Target and web visualization

Fanless CPU and system cooling, natural convection-based passive cooling

Slot for SD card

Integrated Runtime visualization software license Fitted with: 1 x CANopen@/easyNet (built-in interfaces)

1 x RS485 (built-in interface)

Message indication

Printer output

Color display

1 x USB host 2.0 (built-in interface)

2 x Ethernet 10/100 Mbps (built-in interface)

Recipes

1 x PROFIBUS/MPI (built-in interface)

MPI interface

1 x RS232 (built-in interface)

SW interfaces

1 x USB device (built-in interface)

Message system (incl. buffer and confirmation) Functions Additional software components, loadable

Process value representation (output) possible

Process default value (input) possible General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection IP20, rear (according to EN 60529-1)

NEMA 4X

NEMA 12 Degree of protection (front side) IP65

NEMA 12 Fuse type Built-in fuse (not accessible) Lifespa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-15-C02-A00-1C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.