

INDUSTRIAL COMPONENT DATA

XV-303-15-CE0-A00-1E 191079 Y7-191079 EATON ELECTRIC

User interface with PLC as SWD coord.,24 VDC,15.6z PCT ..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-15-CE0-A00-1E



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-15-CE0-A00-1E
Catalog number	Y7-191079
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-18A0024BD4
Generated	2026-08-04

Product Overview

User interface with PLC as SWD coord.,24 VDC,15.6z PCT widesc. display,1366x768 pixels,2xEthernet,1xRS232,1xRS485,1xCAN, 1xSWD,1xSD,VisualDesig
XV-303-15-CE0-A00-1E

Multi-Touch Display with PLC, XV-303, Product range: XV300 15.6z, Subrange: SmartWire-DT touch display with integrated controller (HMI PLC), Function: SmartWire-DT coordinator, Description: XV300 multi touch display with PLC function for flush mounting plates, Control panel with PLC as a SmartWire-DT coordinator and 2nd Ethernet port, Software (Engineering): visualization = Visual Designer, Common features of the model series: Ethernet interface, CAN, USB device, USB Host, RS232, RS485, Slot for SD card, Operating System Windows Embedded Compact 7 pro, Integrated VisualDesigner Runtime visualization software license , Display - Type: Color display, TFT, anti-glare, Touch-technology: Capacitive multi-touch technology (PCT), Number of colors: 16777216 (Color depth 24 bit), Resolution: WXGA, 1366 x 768 Pixel, Portrait format: yes, Screen diagonal: 15.6, widescreen Inch, Glass panel in aluminum bezel with die-cast aluminum enclosure and plastic enclosure, Operating system: Windows Embedded Compact 7 Pro, PLC-license: PLC license inclusive, License certificates for onboard interfaces: Not required, built-in interfaces: 2 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen®/easyNet...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > HMI Touch Terminals

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 191079 Model Code XV-303-15-CE0-A00-1E EAN

7640130099180 Product Length/Depth 403.7 mm Product Height 76.6 mm Product Width 254.9 mm Product Weight 3.9 kg

Certifications CUL

IEC/EN 61131-2

EMC according to 2014/30/EU

DNV GL

EN 50178 Features & Functions

Enclosure material Aluminum (die-cast, glass panel)

Insulated material Features RS232

Target and web visualization

Ethernet interface

USB Host

RS485

CAN

Overload proof

Operating System Windows Embedded Compact 7 pro

USB device

Fanless CPU and system cooling, natural convection-based passive cooling

Portrait format

Slot for SD card

Integrated VisualDesigner Runtime visualization software license Fitted with: SW interfaces

1 x USB device (built-in interface)

Color display

1 x USB host 2.0 (built-in interface)

Message system (incl. buffer and confirmation)

1 x CANopen®/easyNet (built-in interfaces)

1 x SmartWire-DT (built-in interface)

Message indication

Recipes

1 x RS232 (built-in interface)

1 x RS485 (built-in interface)

Printer output

2 x Ethernet 10/100 Mbps (built-in interface) Functions Process default value (input) possible

SmartWire-DT coordination

Additional software components, loadable

Process value representation (output) possible General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection IP20, rear (according to EN 60529-1)

NEMA 12

NEMA 4X Degree of protection (front side) NEMA 12

IP65 Fuse t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-15-CE0-A00-1E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.