

INDUSTRIAL COMPONENT DATA

XV-303-15-CE2-A00-1C 191076 Y7-191076 EATON ELECTRIC

User interface with PLC as an SWD coordinator,24VDC,15...

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-15-CE2-A00-1C



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-15-CE2-A00-1C
Catalog number	Y7-191076
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-AA050783B7
Generated	2026-08-05

Product Overview

User interface with PLC as an SWD coordinator,24VDC,15.6-inch PCT widescreen display,1366x768,2xEthernet,1xRS232,1xRS485,1xCAN,1xSWD,1xProfibus,1xSD
XV-303-15-CE2-A00-1C

Multi-Touch Display with PLC, XV-303, Product range: XV300 15.6z, Subrange: SmartWire-DT touch display with integrated controller (HMI PLC), Function: SmartWire-DT coordinator, Description: XV300 multi touch display with PLC function for flush mounting plates, Control panel with PLC as a SmartWire-DT coordinator with PROFIBUS and 2nd Ethernet port, Common features of the model series: Ethernet interface, CAN, USB device, USB Host, RS232, RS485, Slot for SD card, Operating System Windows Embedded Compact 7 pro, Integrated Runtime visualization software license, Display - Type: Color display, TFT, anti-glare , Touch-technology: Capacitive multi-touch technology (PCT), Number of colors: 16777216 (Color depth 24 bit), Resolution: WXGA, 1366 x 768 Pixel, Portrait format: yes, Screen diagonal: 15.6, widescreen Inch, Glass panel in aluminum bezel with die-cast aluminum enclosure and plastic enclosure, Operating system: Windows Embedded Compact 7 Pro, PLC-license: PLC license inclusive, License certificates for onboard interfaces: Not required, built-in interfaces: 2 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen@/easyNet, 1 x PROFIBUS/MPI, 1 x SmartWire-DT , Front type: No...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 191076 Model Code XV-303-15-CE2-A00-1C EAN

7640130099159 Product Length/Depth 403.7 mm Product Height 76.6 mm Product Width 254.9 mm Product Weight 3.9 kg

Certifications EN 50178

CUL

DNV GL

EMC according to 2014/30/EU

IEC/EN 61131-2 Features & Functions

Enclosure material Aluminum (die-cast, glass panel)

Insulated material Features Fanless CPU and system cooling, natural convection-based passive cooling

Portrait format

USB Host

Target and web visualization

Integrated Runtime visualization software license

CAN

Operating System Windows Embedded Compact 7 pro

USB device

Overload proof

RS485

Slot for SD card

Ethernet interface

RS232 Fitted with: 1 x RS232 (built-in interface)

2 x Ethernet 10/100 Mbps (built-in interface)

SW interfaces

Color display

Message system (incl. buffer and confirmation)

1 x RS485 (built-in interface)

1 x SmartWire-DT (built-in interface)

MPI interface

Recipes

Printer output

1 x PROFIBUS/MPI (built-in interface)

1 x USB host 2.0 (built-in interface)

Message indication

1 x USB device (built-in interface)

1 x CANopen®/easyNet (built-in interfaces) Functions Process value representation (output) possible

Process default value (input) possible

Additional software components, loadable

SmartWire-DT coordination General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection NEMA 4X

IP20, rear (according to EN 60529-1)

NEMA 12 Degree of protec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-15-CE2-A00-1C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.