

INDUSTRIAL COMPONENT DATA

XV-303-70-C02-A00-1B 179652 Y7-179652 EATON ELECTRIC

Control panel, 24 VDC, 7 Inches PCT-Display, 1024x600, ..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-70-C02-A00-1B



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-70-C02-A00-1B
Catalog number	Y7-179652
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-B7DF8754DB
Generated	2026-08-06

Product Overview

Control panel, 24 VDC, 7 Inches PCT-Display, 1024x600, 2xEthernet, 1xRS232, 1xRS485, 1xCAN, 1xProfibus, 1xSD card slot

XV-303-70-C02-A00-1B

Multi-Touch Display, XV-303, Product range: XV300 7z, Function: HMI-PLC (PLC retrofitted by user), Control panel with PROFIBUS and 2nd Ethernet port, Common features of the model series: Ethernet interface, CAN, USB device, USB Host, RS232, RS485, Slot for SD card, Operating System Windows Embedded Compact 7 pro, Integrated Runtime visualization software license, Display - Type: Color display, TFT, anti-glare, Touch-technology: Capacitive multi-touch technology (PCT), Number of colors: 16777216 (Color depth 24 bit), Resolution: WSVGA, 1024 x 600 Pixel, Portrait format: yes, Screen diagonal: 7, widescreen Inch , Plastic enclosure and glass panel in plastic frame, Operating system: Windows Embedded Compact 7 Pro, PLC-license: Can be fitted by user with article no. 181585 LIC-PLC-A, License certificates for onboard interfaces: Not required, built-in interfaces: 2 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen@/easyNet, 1 x PROFIBUS/MPI, Front type: Anti-glare tempered glass in plastic bezel, Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 181638, Pluggable communication cards (optional): no, Touch sensor: Multi-touch touch panel , H...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > HMI Touch Terminals**

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 179652 Model Code XV-303-70-C02-A00-1B EAN

7640130098671 Product Length/Depth 196 mm Product Height 51 mm Product Width 135 mm Product Weight 0.81 kg

Certifications UL File No.: E205091

DNV GL

UL

CE

EMC according to 2014/30/EU

Certified by UL for use in Canada

UL 61010-2-201

IEC/EN 61131-2

CUL

EN 50178 Features & Functions

Enclosure material Insulated material Features Slot for SD card

Target and web visualization

CAN

USB device

Portrait format

USB Host

RS485

Integrated Runtime visualization software license

Fanless CPU and system cooling, natural convection-based passive cooling

RS232

Operating System Windows Embedded Compact 7 pro

Ethernet interface Fitted with: SW interfaces

1 x USB host 2.0 (built-in interface)

2 x Ethernet 10/100 Mbps (built-in interface)

1 x RS232 (built-in interface)

Printer output

MPI interface

Message system (incl. buffer and confirmation)

1 x PROFIBUS/MPI (built-in interface)

1 x CANopen®/easyNet (built-in interfaces)

1 x RS485 (built-in interface)

Color display

Message indication

Recipes

1 x USB device (built-in interface) Functions Process value representation (output) possible

Process default value (input) possible

Additional software components, loadable General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection NEMA 4X

IP20, rear (according to EN 60529-1)

NEMA 12 Degree of protection (front side) IP65

NEMA 12 Fuse type....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-70-C02-A00-1B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.