

INDUSTRIAL COMPONENT DATA

XV-303-70-CE0-A00-1C 179656 Y7-179656 EATON ELECTRIC

Control panel with PLC as SWD coordinator, 24 VDC, 7 In..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-70-CE0-A00-1C



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-70-CE0-A00-1C
Catalog number	Y7-179656
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-C4DA13497A
Generated	2026-08-05

Product Overview

Control panel with PLC as SWD coordinator, 24 VDC, 7 Inches PCT-Display, 1024x600 pixels, 1xEthernet, 1xRS232, 1xRS485, 1xCAN, 1xSWD,1xSD card slot
XV-303-70-CE0-A00-1C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > HMI Touch Terminals**

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 179656 Model Code XV-303-70-CE0-A00-1C EAN 7640130098701 Product Length/Depth 196 mm Product Height 51 mm Product Width 135 mm Product Weight 0.84 kg
Certifications EN 50178
UL 61010-2-201
CE
DNV GL
IEC/EN 61131-2
CUL
EMC according to 2014/30/EU
UL
UL File No.: E205091
Certified by UL for use in Canada Features & Functions

Enclosure material Insulated material Features USB device
RS232
Slot for SD card
Target and web visualization
Integrated Runtime visualization software license
Fanless CPU and system cooling, natural convection-based passive cooling
USB Host
Overload proof
RS485
Operating System Windows Embedded Compact 7 pro
Portrait format
Ethernet interface
CAN Fitted with: 1 x USB device (built-in interface)
1 x CANopen®/easyNet (built-in interfaces)
1 x USB host 2.0 (built-in interface)
2 x Ethernet 10/100 Mbps (built-in interface)
1 x RS485 (built-in interface)
1 x SmartWire-DT (built-in interface)
SW interfaces
Message indication
Message system (incl. buffer and confirmation)
Recipes
Printer output
1 x RS232 (built-in interface)
Color display Functions Process value representation (output) possible
Process default value (input) possible
SmartWire-DT coordination
Additional software components, loadable General
Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection IP20, rear (according to EN 60529-1)
NEMA 12
NEMA 4X Degree of protection (front si...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-70-CE0-A00-1C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.