

**INDUSTRIAL COMPONENT DATA**

# XV-303-70-CE0-A00-1C 179656 Y7-179656 EATON ELECTRIC

## Control panel with PLC as SWD coordinator, 24 VDC, 7 In..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-70-CE0-A00-1C



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | EATON - MOELLER      |
| MPN / Reference | XV-303-70-CE0-A00-1C |
| Catalog number  | Y7-179656            |
| Category        | Graphic panel        |
| Minimum order   | 1 Pcs                |
| Document ID     | EO-C4DA13497A        |
| Generated       | 2026-08-06           |

### Product Overview

Control panel with PLC as SWD coordinator, 24 VDC, 7 Inches PCT-Display, 1024x600 pixels, 1xEthernet, 1xRS232, 1xRS485, 1xCAN, 1xSWD,1xSD card slot  
XV-303-70-CE0-A00-1C

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > HMI Touch Terminals**

### Additional Product Information

**General specifications**

Product Name Eaton XV-303 Touch panel Catalog Number 179656 Model Code XV-303-70-CE0-A00-1C EAN 7640130098701 Product Length/Depth 196 mm Product Height 51 mm Product Width 135 mm Product Weight 0.84 kg  
Certifications EN 50178  
UL 61010-2-201  
CE  
DNV GL  
IEC/EN 61131-2  
CUL  
EMC according to 2014/30/EU  
UL  
UL File No.: E205091  
Certified by UL for use in Canada Features & Functions

Enclosure material Insulated material Features USB device  
RS232  
Slot for SD card  
Target and web visualization  
Integrated Runtime visualization software license  
Fanless CPU and system cooling, natural convection-based passive cooling  
USB Host  
Overload proof  
RS485  
Operating System Windows Embedded Compact 7 pro  
Portrait format  
Ethernet interface  
CAN Fitted with: 1 x USB device (built-in interface)  
1 x CANopen®/easyNet (built-in interfaces)  
1 x USB host 2.0 (built-in interface)  
2 x Ethernet 10/100 Mbps (built-in interface)  
1 x RS485 (built-in interface)  
1 x SmartWire-DT (built-in interface)  
SW interfaces  
Message indication  
Message system (incl. buffer and confirmation)  
Recipes  
Printer output  
1 x RS232 (built-in interface)  
Color display Functions Process value representation (output) possible  
Process default value (input) possible  
SmartWire-DT coordination  
Additional software components, loadable General  
Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection IP20, rear (according to EN 60529-1)  
NEMA 12  
NEMA 4X Degree of protection (front si...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-70-CE0-A00-1C with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.