

INDUSTRIAL COMPONENT DATA

XV-303-70-CE2-A00-1C 179658 Y7-179658 EATON ELECTRIC

Control panel with PLC as SWD coordinator, 24 VDC, 7 In..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-303-70-CE2-A00-1C



Manufacturer	EATON - MOELLER
MPN / Reference	XV-303-70-CE2-A00-1C
Catalog number	Y7-179658
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-8ABD463A64
Generated	2026-08-06

Product Overview

Control panel with PLC as SWD coordinator, 24 VDC, 7 Inches PCT-Display, 1024x600, 2xEthernet, 1xRS232, 1xRS485, 1xCAN,1xSWD, 1xProfibus

XV-303-70-CE2-A00-1C

SWD multi-touch display with PLC, XV-303, Product range: XV300 7z, Subrange: SmartWire-DT touch display with integrated controller (HMI PLC), Function: SmartWire-DT coordinator, Description: XV300 multi touch display with PLC function for flush mounting plates, Control panel with PLC as a SmartWire-DT coordinator with PROFIBUS and 2nd Ethernet port, Common features of the model series: Ethernet interface, CAN, USB device, USB Host, RS232, RS485, Slot for SD card, Operating System Windows Embedded Compact 7 pro, Integrated Runtime visualization software license, Display - Type: Color display, TFT, anti-glare , Touch-technology: Capacitive multi-touch technology (PCT), Number of colors: 16777216 (Color depth 24 bit), Resolution: WSVGA, 1024 x 600 Pixel, Portrait format: yes, Screen diagonal: 7, widescreen Inch, Plastic enclosure and glass panel in plastic frame, Operating system: Windows Embedded Compact 7 Pro, PLC-license: PLC license inclusive, License certificates for onboard interfaces: Not required, built-in interfaces: 2 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen®/easyNet, 1 x PROFIBUS/MPI, 1 x SmartWire-DT, Front type: Anti-glare tempered glass in plastic bezel, Utiliz...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > HMI Touch Terminals**

Additional Product Information

General specifications

Product Name Eaton XV-303 Touch panel Catalog Number 179658 Model Code XV-303-70-CE2-A00-1C EAN

7640130098718 Product Length/Depth 196 mm Product Height 51 mm Product Width 135 mm Product Weight 0.84 kg

Certifications CUL

DNV GL

UL File No.: E205091

Certified by UL for use in Canada

UL

EMC according to 2014/30/EU

IEC/EN 61131-2

EN 50178

UL 61010-2-201

CE Features & Functions

Enclosure material Insulated material Features RS232

Target and web visualization

Slot for SD card

CAN

Portrait format

USB Host

Overload proof

Ethernet interface

Operating System Windows Embedded Compact 7 pro

Integrated Runtime visualization software license

Fanless CPU and system cooling, natural convection-based passive cooling

USB device

RS485 Fitted with: SW interfaces

Color display

Message indication

1 x USB device (built-in interface)

1 x PROFIBUS/MPI (built-in interface)

1 x RS485 (built-in interface)

Recipes

1 x USB host 2.0 (built-in interface)

MPI interface

Message system (incl. buffer and confirmation)

1 x RS232 (built-in interface)

Printer output

1 x CANopen®/easyNet (built-in interfaces)

1 x SmartWire-DT (built-in interface)

2 x Ethernet 10/100 Mbps (built-in interface) Functions SmartWire-DT coordination

Process value representation (output) possible

Process default value (input) possible

Additional software components, loadable General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection NEMA 12

NEMA 4X

IP20, rear (acc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-303-70-CE2-A00-1C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.