

INDUSTRIAL COMPONENT DATA

**XV-363-12-C02-A00-1B 197669 Y7-197669 EATON ELECTRIC
XV-363-12-C02-A00-1B**

Brand: EATON - MOELLER | Manufacturer Part Number: XV-363-12-C02-A00-1B



Manufacturer	EATON - MOELLER
MPN / Reference	XV-363-12-C02-A00-1B
Catalog number	Y7-197669
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-27FB8ADA55
Generated	2026-08-05

Product Overview

XV-363-12-C02-A00-1B

Eaton XV-363 Single touch display, 12-inch display, 24 VDC, IR, 800 x 600 pixels, 2x Ethernet, 1x RS232, 1x RS485, 1x CAN, 1x DP, PLC function can be fitted by user

12.1z infrared touch panel in 4:3 format; built-in unit; resolution 800 x 600 pixels; Can be used in portrait or landscape mode; PLC function can be retrofitted with article no. 181585 LIC-PLC-A; laminated safety glass in aluminum front; robust and easy to clean; metal housing; SD card slot; operating system: Windows Embedded Compact 7 Pro; two independent Ethernet interfaces for safe isolation of the higher-level IT communication and machine network; other interfaces: CAN, Profibus-DP, RS232, RS485; USB host 2.0, USB device; can be configured with Galileo and XSOFT-CODESYS-2/3; integrated runtime license for visualization; degree of protection at front: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-363 Touch panel Catalog Number 197669 Model Code XV-363-12-C02-A00-1B EAN

7640130099401 Product Length/Depth 361 mm Product Height 100 mm Product Width 279 mm Product Weight 2.2 kg

Certifications EN 50178

IEC/EN 61131-2

EAC Catalog Notes Current consumption at 24 V DC Features & Functions

Features USB device

USB Host
Ethernet interface
PLC function can be fitted by user
CAN
Fanless CPU and system cooling, natural convection-based passive cooling
Portrait format
RS232
Slot for SD card
RS485 Fitted with: Recipes
1 x USB device (built-in interface)
1 x RS485 (built-in interface)
Message system (incl. buffer and confirmation)
1 x CAN (built-in interfaces)
MPI interface
Numeric keyboard
Color display
Message indication
1 x PROFIBUS (built-in interface)
1 x RS232 (built-in interface)
1 x USB host 2.0 (built-in interface)
2 x Ethernet 10/100 Mbps (built-in interface)
Alpha numeric keyboard Functions Additional software components, loadable
Process default value (input) possible
Process value representation (output) possible General
Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection IP20, rear (according to EN 60529-1) Degree of protection (front side) IP65
NEMA 12 Fuse type Built-in fuse (not accessible) Model Metal enclosure and glass front in aluminum frame Mounting method Flush mounting - Clearance: Width x Height x Depth ≥ 30 mm (1.18")
Flush mounting Product category XV-300 RoHs conf...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-363-12-C02-A00-1B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.