

INDUSTRIAL COMPONENT DATA

**XV-363-57-C02-A00-1B 197667 Y7-197667 EATON ELECTRIC
XV-363-57-C02-A00-1B**

Brand: EATON - MOELLER | Manufacturer Part Number: XV-363-57-C02-A00-1B



Manufacturer	EATON - MOELLER
MPN / Reference	XV-363-57-C02-A00-1B
Catalog number	Y7-197667
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-F46DFB2B73
Generated	2026-08-05

Product Overview

XV-363-57-C02-A00-1B

Eaton XV-363 Single touch display, 5.7-inch display, 24 VDC, IR, 640 x 480 pixels, 2x Ethernet, 1x RS232, 1x RS485, 1x CAN, 1x DP, PLC function can be fitted by user

5.7z infrared touch panel in 4:3 format; built-in unit; resolution 640 x 480 pixels; can be used portrait or landscape; PLC function can be retrofitted with article no. 181585 LIC-PLC-A; laminated safety glass in aluminum front; robust and easy to clean; metal housing; SD card slot; operating system: Windows Embedded Compact 7 Pro; two independent Ethernet interfaces for safe isolation of the higher-level IT communication and machine network; other interfaces: CAN, Profibus-DP, RS232, RS485; USB host 2.0 , USB device; can be configured with Galileo and XSOFT-CODESYS-2/3; integrated runtime license for visualization; degree of protection at front: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > HMI Touch Terminals

Additional Product Information

General specifications

Product Name Eaton XV-363 Touch panel Catalog Number 197667 Model Code XV-363-57-C02-A00-1B EAN

7640130099364 Product Length/Depth 212 mm Product Height 60 mm Product Width 156 mm Product Weight 1.2 kg

Certifications IEC/EN 61131-2

EN 50178

EAC Catalog Notes Current consumption at 24 V DC Features & Functions

Features Fanless CPU and system cooling, natural convection-based passive cooling

PLC function can be fitted by user

Portrait format

USB Host

RS485

Ethernet interface

RS232

CAN

USB device

Slot for SD card Fitted with: Numeric keyboard

1 x USB host 2.0 (built-in interface)

Color display

1 x CAN (built-in interfaces)

MPI interface

2 x Ethernet 10/100 Mbps (built-in interface)

1 x USB device (built-in interface)

Alpha numeric keyboard

1 x PROFIBUS (built-in interface)

1 x RS232 (built-in interface)

1 x RS485 (built-in interface)

Message indication

Message system (incl. buffer and confirmation)

Recipes Functions Process default value (input) possible

Process value representation (output) possible

Additional software components, loadable General

Battery runtime Back-up of real-time clock: BR 2330, non-replaceable (soldered) Degree of protection IP20, rear (according to EN 60529-1) Degree of protection (front side) IP65

NEMA 12 Fuse type Built-in fuse (not accessible) Model Metal enclosure and glass front in aluminum frame Mounting method Flush mounting

Flush mounting - Clearance: Width x Height x Depth $\geq$ 30 mm (1.18") Product category XV-300 RoHs confo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-363-57-C02-A00-1B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.