

INDUSTRIAL COMPONENT DATA

XV-112-D6-57TVRC-00 153469 EATON ELECTRIC Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS485, CAN,..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-112-D6-57TVRC-00



Manufacturer	EATON - MOELLER
MPN / Reference	XV-112-D6-57TVRC-00
Catalog number	153469
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-B34F1D6D21
Generated	2026-08-04

Product Overview

Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS485, CAN, PLC, rear mounting
Touch Terminal; 5.7"; Resistive; TFT Color; Ethernet; RS232; RS485; DOG; PLC license included; Rear Mount
User interface, XV-112, Product range: XV100 5.7z, Function: HMI-PLC (PLC integrated), Common features of the model series: Ethernet interface, USB device, USB Host, Slot for SD card, UL508, cUL approvals, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colors: 64 k Colors, Resolution: VGA, 640 x 480 Pixel, Portrait format: yes, Screen diagonal: 5.7 Inch, Metal enclosure, Operating system: Windows CE 5.0 (license incl.), PLC-license: PLC license inclusive, License certificates for onboard interfaces: Not required, built-in interfaces: 1 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen®/easyNet, Front type: without front plate, Utilization: Rear mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 139807, Pluggable communication cards (optional): no, Touch sensor: Glass with film, Heat dissipation: 9.5 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS485, CAN, PLC, rear mounting User interface, XV-112, Product range: XV100 5.7", Function: HMI-PLC (PLC integrated), Common features of the model series: Ethernet interface, USB device, USB Host, Slot for SD card, UL508, cUL approvals, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colours: 64 k Colours, Resolution: VGA, 640 x 480 Pixel, Portrait format: yes, Screen diagonal: 5.7 Inch, Metal enclosure, Operating system: Windows CE 5.0 (licence incl.), PLC-licence: PLC licence inclusive, License

certificates for onboard interfaces: Not required, built-in interfaces: 1 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x USB host 2.0, 1 x USB device, 1 x CANopen®/easyNet, Front type: without front plate, Utilization: Rear mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 139807, Pluggable communication cards (optional): no, Touch sensor: Glass with film, Heat dissipation: 9.5 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear) Delivery program

Product range XV100 5.7" Product range XV-112 Function HMI-PLC (integrated SPS function) Common features of the model series Ethernet interface

USB device

USB Host

Slot for SD card

UL508, cUL approvals Display - Type Color display, TFT Touch-technology Resistive-Touch Number of colours 64 k Colours Resolution VGA

640 x 480 Pixel Portrait format yes Screen diagonal 5.7 In...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-112-D6-57TVRC-00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.