

INDUSTRIAL COMPONENT DATA

XV-152-D8-10TVR-10 150610 Y7-150610 EATON ELECTRIC

Touch panel, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, R..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-152-D8-10TVR-10



Manufacturer	EATON - MOELLER
MPN / Reference	XV-152-D8-10TVR-10
Catalog number	Y7-150610
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-CB640BD39B
Generated	2026-08-05

Product Overview

Touch panel, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, RS485, profibus, (PLC)

XV-152-D8-10TVR-10

User interface, XV-152, Product range: XV150 10.4z, Function: HMI-PLC (PLC retrofitted by user), Common features of the model series: Ethernet interface, USB device, USB Host, Slot for SD card, UL508, cUL approvals, Display - Type: Color display, TFT, Touch-technology: Resistive-Touch, Number of colors: 64 k Colors, Resolution: VGA, 640 x 480 Pixel, Portrait format: yes, Screen diagonal: 10.4 Inch, Metal enclosure and front plate, Operating system: Windows CE 5.0 (license incl.), PLC-license: Can be fitted by user with article no. 142581 LIC-PLC-MXP-COMPACT, License certificates for onboard interfaces: Not required , built-in interfaces: 1 x Ethernet 10/100 Mbps, 1 x RS232, 1 x RS485, 1 x PROFIBUS/MPI, 1 x USB host 2.0, 1 x USB device, Front type: Standard front with standard membrane (fully enclosed), Utilization: Flush mounting, Slots: for SD card: 1, Memory card automation: Optionally with SD card -> article no. 139807, Pluggable communication cards (optional): no, Touch sensor: Glass with film, Heat dissipation: 14.5 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP65 (at front), IP20 (at rear), Enclosure Type 4X (Indoor use only)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XV-152 Touch panel Catalog Number 150610 Model Code XV-152-D8-10TVR-10 EAN

7640130097209 Product Length/Depth 345 mm Product Height 54 mm Product Width 260 mm Product Weight 2.95 kg

Certifications IEC/EN 61000-6-2

UL508

Certified by UL for use in Canada

UL

UL 508

CSA Class No.: none

DNV GL

EN 50178

IEC/EN 61131-2, CE

CUL508

CSA File No.: UL report applies to both US and Canada

EN 60950

IEC/EN 60950

UL 60950

ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)

IEC/EN 61000-6-3

Security:

CULus

IEC/EN 60079-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)

UL Category Control No.: NRAQ

IEC/EN 61241-0 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x)

IEC/EN 61000-6-4

IEC/EN 61131-2

UL File No.: E205091

IEC/EN 61241-1 (ATEX 94/9/EG: Zone 22, Category 3D (II 3D Ex tc IIIC T70°C IP6x) Features & Functions

Enclosure material Metal, anodized Features Slot for SD card

Overload proof

Portrait format

Ethernet interface

Fanless CPU and system cooling, natural convection-based passive cooling

USB device

USB Host

UL508, cUL approvals Fitted with: 1 x RS485 (built-in interface)

1 x USB device (built-in interface)

1 x RS232 (built-in interface)

1 x USB host 2.0 (built-in interface)

Numeric keyboard

Alpha numeric keyboard

Message indication

1 x PROFIBUS/MPI (built-in interface)

Message system (incl. buffer and confirmation)

1 x Ethernet 10/100 Mbps (built-in interfaces)

Recipes

Printer output

SW interfaces...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-152-D8-10TVR-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.