

INDUSTRIAL COMPONENT DATA

XV-460-57TQB-1-50 139898 4560815 EATON ELECTRIC Touch panel, ir, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, C..

Brand: EATON - MOELLER | Manufacturer Part Number: XV-460-57TQB-1-50



Manufacturer	EATON - MOELLER
MPN / Reference	XV-460-57TQB-1-50
Catalog number	4560815
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-A4240C6645
Generated	2026-08-06

Product Overview

Touch panel, ir, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, CAN, (PLC), stainless steel
Touch Terminal; 5.7" ; Infrared; TFT Color; Ethernet; RS232; DOG; PLC license not included; Stainless Steel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

Touch panel, ir, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, CAN, (PLC), stainless steel User interface, XV400, Product range: XV400 5.7", Function: HMI-PLC (PLC retrofitted by user), Common features of the model series: Ethernet interface, USB device, RS232, CAN/easyNet, UL508, cUL approvals, PLC function can be fitted by user, Communications scope can be fitted by user with licenses, Display - Type: Color display, TFT, Touch-technology: Infra-red touch, Number of colours: Adjustable: 65536 or 256 colours, Resolution: QVGA, 320 x 240 Pixel, Portrait format: yes, Screen diagonal: 5.7 Inch, Metal enclosure with stainless steel front, Operating system: Windows CE (license required), CompactFlash card required, PLC-licence: Can be fitted by user with article no. 140389 LIC-PLC-MXP-SMALL, License certificates for onboard interfaces: Can be expanded as required, see Accessories -> License product certificates, built-in interfaces: 1 x Ethernet 100base-TX/10base-T, 1 x RS232, 1 x CAN, 1 x USB host, 1 x USB device, Front type: Satin-finish brushed stainless steel, Laminated safety glass, non-reflective, Utilization: Flush mounting, Slots: for Compact-FlashTM-Cards: 1, for communication modules: 1, Memory card automation: required, see Accessories -> Memory cards, Pluggable communication cards (optional): yes, Heat dissipation: 24 W, Degree of protection (IEC/EN 60529, EN50178, VBG 4): IP69K (at front), IP20 (on rear) Delivery program
Product range XV400 5.7" Product range XV400 Funct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XV-460-57TQB-1-50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.