

INDUSTRIAL COMPONENT DATA

XVTL-SH/P/F-10 187967 Y7-187967 EATON ELECTRIC

Residual current circuit breaker (RCCB), 63A, 4p, 30mA, type

..

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-SH/P/F-10



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-SH/P/F-10
Catalog number	Y7-187967
Category	Mounting accessories (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-B4521884C2
Generated	2026-08-06

Product Overview

Residual current circuit breaker (RCCB), 63A, 4p, 30mA, type G/F
XVTL-SH/P/F-10

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

Residual current circuit breaker (RCCB), 63A, 4p, 30mA, type G/F Residual current circuit-breaker PFIM-F, 4 pole, Rated current In: 63 A, Rated short-circuit strength Icn: 10 with back-up fuse kA, Rated fault current I?N: 0.03 A, Switchgear for residential and commercial applications [Delivery program

Basic function Residual current circuit-breakers Number of poles 4 pole Application Residual current circuit-breaker for residential and commercial applications Rated current [In] 63 A Rated short-circuit strength [Icn] 10 with back-up fuse kA Rated fault current [I?N] 0.03 A Type Typ G/F (ÖVE E 8601) Tripping Short time-delayed s... Product range PFIM-F Sensitivity pulse-current sensitive - frequency composition (10 Hz, 50 Hz, 1000 Hz) Impulse withstand current Surge-proof, 3 kA , Technical data

Electrical Types conform to IEC/EN 62423 Current test marks As per inscription Standards IEC/EN 61008 Rated operational voltage [Ue][Ue]Rated operating voltage [Ue] 230/400 V AC Rated voltage according to IEC/EN 60947-2 [Un] 230/400 V AC Rated frequency [f] 50 Hz Limit values of the operating voltageTest circuit 196 - 264 V AC Limit values of the operating voltageComment for range of the test button 3-phase application without N (400V AC Phase-Phase) not allowed

Sensitivity pulse-current sensitive - frequency composition (10 Hz, 50 Hz, 1000 Hz) Rated insulation voltage [Ui] 440 V
Rated impulse withstand voltage [Uimp] 4 kV Rated short-circuit strength [Icn] 10 with back-up fuse kA Max.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-SH/P/F-10 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.