

INDUSTRIAL COMPONENT DATA

Z-BB/UL18/2P1MU/56 171129 Y7-171129 EATON ELECTRIC

Phase busbar, 2-phase, 18qmm, pin, 1m

Brand: EATON - MOELLER | Manufacturer Part Number: Z-BB/UL18/2P1MU/56



Manufacturer	EATON - MOELLER
MPN / Reference	Z-BB/UL18/2P1MU/56
Catalog number	Y7-171129
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-DFFFAC5D8D
Generated	2026-08-04

Product Overview

Phase busbar, 2-phase, 18qmm, pin, 1m

Z-BB/UL18/2P1MU/56

Block busbar for FAZ-NA/RT, supplied without end caps, type conforms to UL489, EN 60947-1, IEC 60947-1:2004

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Phase busbar, 2-phase, 18qmm, pin, 1mBlock busbar for FAZ-NA/RT, supplied without end caps, type conforms to UL489, EN 60947-1, IEC 60947-1:2004

General specificationsProduct nameEaton Moeller series busbarPart no.Z-BB/UL18/2P1MU/56EAN4015081676194Product Length/Depth992.2 millimetreProduct height56.8 millimetreProduct width19.3 millimetreProduct weight0.879

kilogramCompliancesRoHS conformProduct TradenameNoneProduct TypeBusbarProduct Sub TypeNoneProduct

Specification DetailsAccessory/spare part typeBusbar for miniature circuit breakerAmbient operating temperature - max100

°CAmbient operating temperature - min-5 °CApplicationSwitchgear for industrial and advanced commercial

applicationsColorOtherConditioned rated short-circuit current Iq [7EF001444]kAConductor cross section - maxmm²Cross

section18 mm²Cross section [7EF000649]mm²Electric connection typePinFeaturesInsulatedFunctionsBusbarHeat

dissipation capacity0 WHeat dissipation per pole, current-dependent0 WLength [7EF001438]mmMax. rated operation

voltage Ue [7EF007357]VNumber of modular spacings1Number of phases2Number of polesTwo-polePitch dimensions17.6

mmPitch dimensions [7EF007504]mmRated conditional short-circuit current (Iq)0 kARated operational voltage (Ue) -

max600 VRated permanent current Iu [7EF001389]ARated short-time withstand current (Icw)0 kARated short-time

withstand current I_{cw} [7EF007050]kARated surge voltage10 kVRated surge voltage [7EF002993]kVRated uninterrupted current (I_u)80 AStatic heat dissipation,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-BB/UL18/2P1MU/56 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.