

INDUSTRIAL COMPONENT DATA

**Z-BB/UL18/2X1P1MU+AUX/38 171142 Y7-171142 EATON
ELECTRIC Phase busbar, 2x1-phase+HS, 18qmm, pin, 1m**

Brand: EATON - MOELLER | Manufacturer Part Number: Z-BB/UL18/2X1P1MU+AUX/38



Manufacturer	EATON - MOELLER
MPN / Reference	Z-BB/UL18/2X1P1MU+AUX/38
Catalog number	Y7-171142
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-0585DC8ED8
Generated	2026-08-05

Product Overview

Phase busbar, 2x1-phase+HS, 18qmm, pin, 1m

Z-BB/UL18/2X1P1MU+AUX/38

Block busbar for FAZ-NA/RT, supplied without end caps, type conforms to UL489, EN 60947-1, IEC 60947-1:2004

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Phase busbar, 2x1-phase+HS, 18qmm, pin, 1m Block busbar for FAZ-NA/RT, supplied without end caps, type conforms to UL489, EN 60947-1, IEC 60947-1:2004 Delivery program

Basic function Busbar Basic function accessories Busbar for miniature circuit-breaker Application Switchgear for industrial and advanced commercial applications Busbar type Single-phase + auxiliary contact Product range Z-BB/UL Design verification as per IEC/EN 61439

Heat dissipation per pole, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -5 °C Operating ambient temperature max. +100 °C Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215) Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar ( [ACN992011]) Number of phases 2 Number of poles 2 Suitable for number of devices 0 Pitch dimensions 26.4 mm Cross section 18 mm² Length 1000 mm Number of modular spacings 1 Rated permanent current Iu 80 A Type of electric connection Pin Insulated Yes Rated surge voltage 10 kV Conditioned rated short-circuit current Iq 0 kA Max. rated

operation voltage Ue 600 V Rated short-time withstand current Icw 0 kA Suitable for devices with N-busbar No Suitable for devices with auxiliary switch Yes

ETIM for 171142 Low-voltage industrial controls and switchgear...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-BB/UL18/2X1P1MU+AUX/38 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.