

INDUSTRIAL COMPONENT DATA

Z-BB/UL18/3X1P1MU+AUX/39 171140 Y7-171140 EATON ELECTRIC Phase busbar, 3x1-phase+HS, 18qmm, pin, 1m

Brand: EATON - MOELLER | Manufacturer Part Number: Z-BB/UL18/3X1P1MU+AUX/39



Manufacturer	EATON - MOELLER
MPN / Reference	Z-BB/UL18/3X1P1MU+AUX/39
Catalog number	Y7-171140
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-D2776A443D
Generated	2026-08-05

Product Overview

Phase busbar, 3x1-phase+HS, 18qmm, pin, 1m

Z-BB/UL18/3X1P1MU+AUX/39

Block busbar for FAZ-NA/RT, supplied without end caps, type conforms to UL489, EN 60947-1, IEC 60947-1:2004

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Moeller series busbar Catalog Number 171140 Model Code Z-BB/UL18/3X1P1MU+AUX/39 EAN 4015081676293 Product Length/Depth 1027.4 mm Product Height 56.8 mm Product Width 19.3 mm Product Weight 0.959 kg Compliances RoHS conform Product specifications

Used with Busbar

Z-BB/UL Type Features Insulated

Can be cut to size Accessory/spare part type Busbar for miniature circuit breaker Electric connection type Pin Rated surge voltage 10 KV Rated uninterrupted current (Iu) 80 A Static heat dissipation, non-current-dependent 0 W Suitable for number of devices 0 Application Switchgear for industrial and advanced commercial applications Number of poles Three-pole Color Other Rated short-time withstand current (Icw) 0 kA Ambient operating temperature - max 100 °C Ambient operating temperature - min -5 °C Cross section 18 mm² Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Number of modular spacings 1 Number of phases 3 Pitch dimensions 26.4 mm Rated operational voltage (Ue) - max 600 V Rated conditional short-circuit current (Iq) 0 kA Functions Busbar Suitable for Devices with auxiliary switch

ETIM for 171140 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3

Number of poles (EF001391)

3

Suitable for number of devices (EF007241)

0

Module width (EF007504)

26.4 mm

Cross section (EF000649)

18 mm²

Length (EF001438)

1027.4 mm

Can be cut to size (EF015250)

Yes

Wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-BB/UL18/3X1P1MU+AUX/39 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.