

INDUSTRIAL COMPONENT DATA

Z-BB/UL25/1P1MU/57 171131 Y7-171131 EATON ELECTRIC

Phase busbar, 1-phase, 25qmm, pin, 1m

Brand: EATON - MOELLER | Manufacturer Part Number: Z-BB/UL25/1P1MU/57



Manufacturer	EATON - MOELLER
MPN / Reference	Z-BB/UL25/1P1MU/57
Catalog number	Y7-171131
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-A4D1638FB8
Generated	2026-08-04

Product Overview

Phase busbar, 1-phase, 25qmm, pin, 1m

Z-BB/UL25/1P1MU/57

Block busbar for FAZ-NA/RT, supplied without end caps, type conforms to UL489, EN 60947-1, IEC 60947-1:2004

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Phase busbar, 1-phase, 25qmm, pin, 1mBlock busbar for FAZ-NA/RT, supplied without end caps, type conforms to UL489, EN 60947-1, IEC 60947-1:2004

General specifications
Product nameEaton Moeller series busbar
Part no.Z-BB/UL25/1P1MU/57
EAN4015081676217
Product Length/Depth1009.8 millimetre
Product height56.8 millimetre
Product width19.3 millimetre
Product weight0.773 kilogram
CompliancesRoHS conform
Product TradenameNone
Product TypeBusbar
Product Sub TypeNone
Product Specification Details
Accessory/spare part typeBusbar for miniature circuit breaker
Ambient operating temperature - max100 °C
Ambient operating temperature - min-5 °C
ApplicationSwitchgear for industrial and advanced commercial applications
ColorOther
Conditioned rated short-circuit current Iq [7EF001444]kA
Conductor cross section - maxmm²Cross section25 mm²
Cross section [7EF000649]mm²
Electric connection typePin
FeaturesInsulated
FunctionsBusbar
Heat dissipation capacity0 W
Heat dissipation per pole, current-dependent0 W
Length [7EF001438]mm
Max. rated operation voltage Ue [7EF007357]V
Number of modular spacings1
Number of phases1
Number of polesSingle-pole
Pitch dimensions17.6 mm
Pitch dimensions [7EF007504]mm
Rated conditional short-circuit current (Iq)0 kA
Rated operational voltage (Ue) - max1000 V
Rated permanent current Iu [7EF001389]A
Rated short-time withstand current (Icw)0 kA
Rated

short-time withstand current I_{cw} [7EF007050]kARated surge voltage10 kVRated surge voltage [7EF002993]kVRated
uninterrupted current (I_u)100 AStatic heat dissip...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-BB/UL25/1P1MU/57 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.