

INDUSTRIAL COMPONENT DATA

Z-BHASA/24 248444 Y7-248444 EATON ELECTRIC

Z-BHASA/24 Shunt release, 12-60V, 1.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-BHASA/24



Manufacturer	EATON - MOELLER
MPN / Reference	Z-BHASA/24
Catalog number	Y7-248444
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-2055230C3C
Generated	2026-08-05

Product Overview

Z-BHASA/24 Shunt release, 12-60V, 1.5HP

Z-BHASA/24

Eaton Distribution parts. Shunt release, 12-60V, 1.5HP

Shunt release, for residual current circuit-breaker unit, voltage range 12-60V AC / 12-60V DC, minimum pulse duration 15ms, standard front dimension 45 mm, mounting width 1.5 space units (27mm), top-hat rail mounting, terminal cross-section 2.5-30 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248444 Model Code Z-BHASA/24 EAN 4015082484446 Product Length/Depth 80 mm Product Height 75 mm Product Width 39.1 mm Product Weight 0.158 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Shunt release Used with Shunt releases

Accessory for residual current circuit breaker

Accessory Mounting method Can be mounted from left: Mountable residual current circuit breaker Additional equipment required Shunt release (for power circuit breaker) Ambient operating temperature - max 40 °C Ambient operating

temperature - min -5 °C Assembly width 1.5 TE Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC/DC Functions Shunt release (for power circuit breaker) Device fitting Miniature circuit breaker (MCB) Rated operational voltage (Ue) - max 24 V Rated switch current 1.7 A Suitable for current of main contact unit - max 7 A

ETIM for 248444 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Miniature circuit breaker (MCB)

Function (EF000030)

Shunt release (for power circuit breaker)

Width in number of modular spacings (EF002950)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-BHASA/24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.