

## INDUSTRIAL COMPONENT DATA

# Z-GV-10/3P-4TE 271080 Y7-271080 EATON ELECTRIC

## Z-GV-10/3P-4TE

Brand: EATON - MOELLER | Manufacturer Part Number: Z-GV-10/3P-4TE



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | Z-GV-10/3P-4TE  |
| Catalog number  | Y7-271080       |
| Category        | Phase busbar    |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-0AE889C92F   |
| Generated       | 2026-08-04      |

## Product Overview

Z-GV-10/3P-4TE

Busbar, isolated, 63A, 3p, 4Mod

Block busbar for PLS.CLS.PKN.PFIM, PFHM, Z-SLS/D01 (also with auxiliary contact), cover caps are not included as standard

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Modular Switchgear - Others and Accessories

## Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 271080 Model Code Z-GV-10/3P-4TE EAN 4015082710804

Product Length/Depth 25.5 mm Product Height 14.9 mm Product Width 965 mm Product Weight 0.406 kg Compliances

RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Fork Rated surge voltage 0 KV Rated uninterrupted current (Iu) 0 A Suitable for number of devices 39 Number of poles Three-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm<sup>2</sup> Number of modular spacings 5 Number of phases 3 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit current (Iq) 0 kA Suitable for Devices with auxiliary switch

ETIM for 271080 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3

Number of poles (EF001391)

3

Suitable for number of devices (EF007241)

39

Module width (EF007504)

0 mm

Cross section (EF000649)

10 mm<sup>2</sup>

Length (EF001438)

25.5 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

5

Rated permanent current I<sub>u</sub> (EF001389)

0 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

0 kV

Conditioned rated short-circuit current I<sub>q</sub> (EF001444)

0 kA

Max. rated operation voltage U<sub>e</sub> (EF007357)

415 V

Rated short-time withstand current I<sub>cw</sub> (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

No

Suitable for d...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-GV-10/3P-4TE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.