


INDUSTRIAL COMPONENT DATA

Z-GV-16/3P-3TE/6 267511 Y7-267511 EATON ELECTRIC

Z-GV-16/3P-3TE/6

Brand: EATON - MOELLER | Manufacturer Part Number: Z-GV-16/3P-3TE/6



Manufacturer	EATON - MOELLER
MPN / Reference	Z-GV-16/3P-3TE/6
Catalog number	Y7-267511
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-70CB34679D
Generated	2026-08-05

Product Overview

Z-GV-16/3P-3TE/6

Eaton Distribution parts. Busbars, 3p, for SPI and SPC

Busbars: order the cover caps separately short version (17,16,8) including cover caps Length 1 meter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 267511 Model Code Z-GV-16/3P-3TE/6 EAN 4015082675110

Product Length/Depth 32.5 mm Product Height 14.9 mm Product Width 108 mm Product Weight 0.055 kg Compliances

RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Fork Rated surge voltage 4 kV Rated uninterrupted current (I_u) 80 A Suitable for number of devices 9 Number of poles Three-pole Color Other Rated short-time withstand current (I_{cw}) 0 kA Cross section 16 mm² Number of modular spacings 3 Number of phases 3 Pitch dimensions 0 mm Rated operational voltage (U_e) - max 500 V Rated conditional short-circuit current (I_q) 0 kA

ETIM for 267511 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3
Number of poles (EF001391)
3
Suitable for number of devices (EF007241)
9
Module width (EF007504)
0 mm
Cross section (EF000649)
16 mm²
Length (EF001438)
32.5 mm
Can be cut to size (EF015250)
Yes
Width in number of modular spacings (EF002950)
3
Rated permanent current I_u (EF001389)
80 A
Type of electric connection (EF003961)
Fork
Insulated (EF000019)
Yes
Rated surge voltage (EF002993)
4 kV
Conditioned rated short-circuit current I_q (EF001444)
0 kA
Max. rated operation voltage U_e (EF007357)
500 V
Rated short-time withstand current I_{cw} (EF007050)
0 kA
Suitable for devices with N-conductor (EF007218)
No
Suitable for devices with auxiliary switch (EF007217)
N...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-GV-16/3P-3TE/6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.