

INDUSTRIAL COMPONENT DATA

Z-GV-16/3P+HS 271065 Y7-271065 EATON ELECTRIC

Z-GV-16/3P+HS

Brand: EATON - MOELLER | Manufacturer Part Number: Z-GV-16/3P+HS



Manufacturer	EATON - MOELLER
MPN / Reference	Z-GV-16/3P+HS
Catalog number	Y7-271065
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-930C304BE9
Generated	2026-08-06

Product Overview

Z-GV-16/3P+HS

Busbar, isolated, 80A, 3p, +aux. contact

Block busbar for PLS.CLS.PKN.PFIM, PFHM, Z-SLS/D01 (also with auxiliary contact), cover caps are not included as standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 271065 Model Code Z-GV-16/3P+HS EAN 4015082710651

Product Length/Depth 30 mm Product Height 14.9 mm Product Width 1016 mm Product Weight 0.6 kg Compliances RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Fork Rated surge voltage 0 KV Rated uninterrupted current (Iu) 80 A Suitable for number of devices 12 Number of poles Three-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 16 mm² Number of modular spacings 3 Number of phases 3 Pitch dimensions 27 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit current (Iq) 0 kA Suitable for 32 devices

Devices with auxiliary switch

ETIM for 271065 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3

Number of poles (EF001391)

3

Suitable for number of devices (EF007241)

12

Module width (EF007504)

27 mm

Cross section (EF000649)

16 mm²

Length (EF001438)

30 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

3

Rated permanent current I_u (EF001389)

80 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

0 kV

Conditioned rated short-circuit current I_q (EF001444)

0 kA

Max. rated operation voltage U_e (EF007357)

415 V

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

No

Suita...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-GV-16/3P+HS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.