

INDUSTRIAL COMPONENT DATA

Z-SS-60-ADD/6-45 288790 Y7-288790 EATON ELECTRIC 288790 Z-SS-60-ADD/6-45

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SS-60-ADD/6-45



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SS-60-ADD/6-45
Catalog number	Y7-288790
Category	Busbar adapter
Minimum order	1 Pcs
Document ID	EO-DA0F84D3DA
Generated	2026-08-05

Product Overview

288790 Z-SS-60-ADD/6-45

Z-SS-60-ADD/6-45

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Dual adapter, 6-45

Busbar dual adapter, for 60-mm system, with 2x mounting rail, adjustable, center feeder unit per phase 6mm² cable, I_e=32A, width=45mm, for busbars 12x5/10 to 30x5/10, can be used e.g. for DIN fuse devices

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i MCB adapter Catalog Number 288790 Model Code Z-SS-60-ADD/6-45 EAN 4015082887902 Product Length/Depth 182 mm Product Height 80 mm Product Width 47 mm Product Weight 0.34 kg
Compliances RoHS conform Delivery program

Type Nominal current 35 A Technical data - electrical

Voltage rating at AC 690 V AC Rated operation current (I_e) 35 A Electric connection type 3 conductors AWG 10 Technical data - mechanical

Mounting rail armament 2 mounting rails Rail width 30 mm Number of DIN rails 2 Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Busbar adapter width 45 mm Adapter width 45 mm Terminal capacity 6 mm²

Additional information

Functions Busbar dual adapters for modular installation devices

Dual adapter Special features Dual adapter (six 6 mm² connection cables), 2 mounting rails
Mounted by latching onto de-energized busbar
Suitable for Mounting on flat copper busbars with 60 mm interval between busbar centres Used with 12 x 5/10 mm
25 x 5/10 mm
Double T profile
30 x 5/10 mm
15 x 5/10 mm
Suitable for 5 and 10 mm busbar and double T thickness.
20 x 5/10 mm
Busbar dual adapters for modular installation devices
60 mm system
ETIM for 288790 Low-voltage industrial controls and switchgear (EC001531)
Feature Name
Feature Value
Mounting rail armament (EF003700)
2 mounting rails
Type of electric connection (EF003961)
3 conductors AWG 10
Rated current I_n (EF008250)
35 A
Min. busbar thickness (EF006536)
5 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SS-60-ADD/6-45 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.