

INDUSTRIAL COMPONENT DATA

Z-SS-60-ADD/6-81 288793 Y7-288793 EATON ELECTRIC 288793 Z-SS-60-ADD/6-81

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SS-60-ADD/6-81



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SS-60-ADD/6-81
Catalog number	Y7-288793
Category	Busbar adapter
Minimum order	1 Pcs
Document ID	EO-78B6D569E5
Generated	2026-08-02

Product Overview

288793 Z-SS-60-ADD/6-81

Z-SS-60-ADD/6-81

Eaton xEffect SASy 60i Enclosures Switch- & Controlgear Enclosure. Dual adapter, 6-81

Busbar dual adapter, for 60-mm system, with 2x mounting rail, adjustable, center feeder unit per phase 6mm² cable, I_e=32A, width=81mm, for busbars 12x5/10 to 30x5/10, can be used e.g. for DIN fuse devices

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton xEffect SASy 60i MCB adapter Catalog Number 288793 Model Code Z-SS-60-ADD/6-81 EAN 4015082887933 Product Length/Depth 182 mm Product Height 80 mm Product Width 83 mm Product Weight 0.5 kg

Compliances RoHS conform Delivery program

Type Nominal current 35 A Technical data - electrical

Voltage rating at AC 690 V AC Rated operation current (I_e) 35 A Electric connection type 3 conductors AWG 10 Technical data - mechanical

Mounting rail armament 2 mounting rails Rail width 30 mm Number of DIN rails 2 Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Busbar adapter width 81 mm Adapter width 81 mm Terminal capacity 6 mm²

Additional information

Functions Dual adapter

Busbar dual adapters for modular installation devices Special features Dual adapter (six 6 mm² connection cables), 2 mounting rails

Mounted by latching onto de-energized busbar

Suitable for Mounting on flat copper busbars with 60 mm interval between busbar centres Used with Double T profile

12 x 5/10 mm

15 x 5/10 mm

20 x 5/10 mm

25 x 5/10 mm

30 x 5/10 mm

Suitable for 5 and 10 mm busbar and double T thickness.

60 mm system

Busbar dual adapters for modular installation devices

ETIM for 288793 Low-voltage industrial controls and switchgear (EC001531)

Feature Name

Feature Value

Mounting rail armament (EF003700)

2 mounting rails

Type of electric connection (EF003961)

3 conductors AWG 10

Rated current I_n (EF008250)

35 A

Min. busbar thickness (EF006536)

5 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SS-60-ADD/6-81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.