

INDUSTRIAL COMPONENT DATA

Z-SV-35/1P 113135 Y7-113135 EATON ELECTRIC Connecting rods 1 transverse phase grey

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV-35/1P



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV-35/1P
Catalog number	Y7-113135
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-D1768AD8FC
Generated	2026-08-03

Product Overview

Connecting rods 1 transverse phase grey

Eaton Distribution parts. Block busbar, 110A, 35mm², 1-phaseBlock busbar, rated operational current 110A, 35mm², 1-phase

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 113135 Model Code Z-SV-35/1P EAN 4015081126712 Product Length/Depth 1007 mm Product Height 20 mm Product Width 23 mm Product Weight 0.436 kg Compliances RoHS conform

Product specifications

Features Insulated

Can be cut to size Electric connection type Pin Rated surge voltage 6 kV Rated uninterrupted current (I_u) 110 A Suitable for number of devices 2 Number of poles Single-pole Color Other Rated short-time withstand current (I_{cw}) 0 kA Cross section 35 mm² Number of modular spacings 36 Number of phases 1 Pitch dimensions 27 mm Rated operational voltage (U_e) - max 500 V Rated conditional short-circuit current (I_q) 100 kA Suitable for 1 device

ETIM for 113135 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

1
Number of poles (EF001391)
1
Suitable for number of devices (EF007241)
2
Module width (EF007504)
27 mm
Cross section (EF000649)
35 mm²
Length (EF001438)
1007 mm
Can be cut to size (EF015250)
Yes
Width in number of modular spacings (EF002950)
36
Rated permanent current I_u (EF001389)
110 A
Type of electric connection (EF003961)
Pin
Insulated (EF000019)
Yes
Rated surge voltage (EF002993)
6 kV
Conditioned rated short-circuit current I_q (EF001444)
100 kA
Max. rated operation voltage U_e (EF007357)
500 V
Rated short-time withstand current I_{cw} (EF007050)
0 kA
Suitable for devices with N-conductor (EF007218)
No
Suitable for devices with auxilia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV-35/1P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.