

INDUSTRIAL COMPONENT DATA

Z-SV-35/3P 264938 Y7-264938 EATON ELECTRIC 3-phase connecting rods

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV-35/3P



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV-35/3P
Catalog number	Y7-264938
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-DE47277F23
Generated	2026-08-05

Product Overview

3-phase connecting rods

Eaton Distribution parts. Block busbar 3Ph., for Z-SLS, PLHT D0.-SO/.., PLHT-V (1, 5space units)

Block busbar 3Ph., for Z-SLS, PLHT D0.-SO/.., PLHT-V (1.5SU)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 264938 Model Code Z-SV-35/3P EAN 4015082649388 Product Length/Depth 39.3 mm Product Height 19.9 mm Product Width 985 mm Product Weight 1.185 kg Compliances RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Pin Rated surge voltage 4 KV Rated uninterrupted current (Iu) 110 A Suitable for number of devices 2 Number of poles Three-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 35 mm² Number of modular spacings 12 Number of phases 3 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 480 V Rated conditional short-circuit current (Iq) 0 kA

ETIM for 264938 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3
Number of poles (EF001391)
3
Suitable for number of devices (EF007241)
2
Module width (EF007504)
0 mm
Cross section (EF000649)
35 mm²
Length (EF001438)
39.3 mm
Can be cut to size (EF015250)
Yes
Width in number of modular spacings (EF002950)
12
Rated permanent current I_u (EF001389)
110 A
Type of electric connection (EF003961)
Pin
Insulated (EF000019)
Yes
Rated surge voltage (EF002993)
4 kV
Conditioned rated short-circuit current I_q (EF001444)
0 kA
Max. rated operation voltage U_e (EF007357)
480 V
Rated short-time withstand current I_{cw} (EF007050)
0 kA
Suitable for devices with N-conductor (EF007218)
No
Suitable for devices with auxiliary switch (EF007217)
No
Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV-35/3P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.