

INDUSTRIAL COMPONENT DATA

Z-SV/UL-16/1P-1TE/12 104893 Y7-104893 EATON ELECTRIC Block busbar 1Ph., 12HP, for FAZ-NA, FAZ-RT

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV/UL-16/1P-1TE/12



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV/UL-16/1P-1TE/12
Catalog number	Y7-104893
Category	Phase busbar
Minimum order	10 Pcs
Document ID	EO-A4D6EF9887
Generated	2026-08-06

Product Overview

Block busbar 1Ph., 12HP, for FAZ-NA, FAZ-RT

Z-SV/UL-16/1P-1TE/12

Eaton Distribution parts. Block busbar 1Ph., 12HP, for FAZ-NA, FAZ-RT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 104893 Model Code Z-SV/UL-16/1P-1TE/12 EAN 4015081047031

Product Length/Depth 206 mm Product Height 46 mm Product Width 15.5 mm Product Weight 0.108 kg Compliances RoHS conform Certifications UL (File No. E257181)

UL 489

IEC/EN 60898

UL (Category Control Number NMTR2, DIHS2)

UL listed

Specially designed for North America for large creepage and creepage distances

CE marking Product specifications

Type Features Insulated Accessory/spare part type Busbar for residual current circuit breakers

Busbar for miniature circuit breaker

Busbar for combined residual current/power circuit breaker Electric connection type Pin Used with Feeder Circuit, Branch

Circuit

Busbar

Z-SV Rated surge voltage 9.5 KV Rated uninterrupted current (Iu) 0 A Suitable for number of devices 18 Application Switchgear for industrial and advanced commercial applications Number of poles Single-pole Color Other Degree of protection IEC/EN 60898; UL 489; CE marking

IEC: IP20, UL/CSA Type: - Rated short-time withstand current (Icw) 0 kA Voltage rating (UL CSA 13) Refer to main components FAZ, FAZ-NA, FAZ-RT Cross section 16 mm² Number of modular spacings 1 Number of phases 1 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 690 V Rated conditional short-circuit current (Iq) 0 kA Functions

Busbar

ETIM for 104893 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

1

Number o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV/UL-16/1P-1TE/12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.