

INDUSTRIAL COMPONENT DATA

Z-SV/UL-16/1P-1TE/6 104892 Y7-104892 EATON ELECTRIC Block busbar 1Ph., 6HP, for FAZ-NA, FAZ-RT

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV/UL-16/1P-1TE/6



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV/UL-16/1P-1TE/6
Catalog number	Y7-104892
Category	Phase busbar
Minimum order	10 Pcs
Document ID	EO-DBEADC9460
Generated	2026-08-06

Product Overview

Block busbar 1Ph., 6HP, for FAZ-NA, FAZ-RT

Z-SV/UL-16/1P-1TE/6

Eaton Distribution parts. Block busbar 1Ph., 6HP, for FAZ-NA, FAZ-RT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 104892 Model Code Z-SV/UL-16/1P-1TE/6 EAN 4015081047024

Product Length/Depth 100.4 mm Product Height 46 mm Product Width 15.5 mm Product Weight 0.053 kg Compliances

RoHS conform Certifications CE marking

UL listed

UL 489

Specially designed for North America for large creepage and creepage distances

UL (File No. E257181)

IEC/EN 60898

UL (Category Control Number NMTR2, DIHS2) Product specifications

Used with Feeder Circuit, Branch Circuit

Busbar

Z-SV Type Features Insulated Accessory/spare part type Busbar for residual current circuit breakers

Busbar for combined residual current/power circuit breaker

Busbar for miniature circuit breaker Electric connection type Pin Rated surge voltage 9.5 kV Rated uninterrupted current

(I_u) 0 A Suitable for number of devices 6 Application Switchgear for industrial and advanced commercial applications

Number of poles Single-pole Color Other Degree of protection IEC: IP20, UL/CSA Type: -

IEC/EN 60898; UL 489; CE marking Rated short-time withstand current (I_{cw}) 0 kA Voltage rating (UL CSA 13) Refer to main components FAZ, FAZ-NA, FAZ-RT Cross section 16 mm² Number of modular spacings 1 Number of phases 1 Pitch dimensions 0 mm Rated operational voltage (U_e) - max 690 V Rated conditional short-circuit current (I_q) 0 kA Functions

Busbar

ETIM for 104892 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

1

Number o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV/UL-16/1P-1TE/6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.