

INDUSTRIAL COMPONENT DATA

Z-SV/UL-16/2P-2TE/18 104897 Y7-104897 EATON ELECTRIC Block busbar 2Ph., 18HP, for FAZ-NA, FAZ-RT

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV/UL-16/2P-2TE/18



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV/UL-16/2P-2TE/18
Catalog number	Y7-104897
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-1DD610152C
Generated	2026-08-06

Product Overview

Block busbar 2Ph., 18HP, for FAZ-NA, FAZ-RT

Z-SV/UL-16/2P-2TE/18

Eaton Distribution parts. Block busbar 2Ph., 18HP, for FAZ-NA, FAZ-RT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 104897 Model Code Z-SV/UL-16/2P-2TE/18 EAN 4015081047079

Product Length/Depth 311.6 mm Product Height 54 mm Product Width 15.5 mm Product Weight 0.204 kg Compliances

RoHS conform Certifications CE marking

IEC/EN 60898

UL (File No. E257181)

UL (Category Control Number NMTR2, DIHS2)

UL listed

UL 489

Specially designed for North America for large creepage and creepage distances Product specifications

Type Features Insulated Accessory/spare part type Busbar for miniature circuit breaker

Busbar for combined residual current/power circuit breaker

Busbar for residual current circuit breakers Electric connection type Pin Used with Feeder Circuit, Branch Circuit

Busbar

Z-SV Rated surge voltage 9.5 kV Rated uninterrupted current (I_u) 0 A Suitable for number of devices 3 Application

Switchgear for industrial and advanced commercial applications Number of poles Two-pole Color Other Degree of protection IEC: IP20, UL/CSA Type: -

IEC/EN 60898; UL 489; CE marking Rated short-time withstand current (I_{cw}) 0 kA Voltage rating (UL CSA 13) Refer to main components FAZ, FAZ-NA, FAZ-RT Cross section 16 mm² Number of modular spacings 2 Number of phases 2 Pitch dimensions 0 mm Rated operational voltage (U_e) - max 690 V Rated conditional short-circuit current (I_q) 0 kA Functions

Busbar

ETIM for 104897 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

2

Number of....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV/UL-16/2P-2TE/18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.