

INDUSTRIAL COMPONENT DATA

Z-VPS-4/1p+HS 302375 Y7-302375 EATON ELECTRIC Splint HK 1p+HK short pin

Brand: EATON - MOELLER | Manufacturer Part Number: Z-VPS-4/1p+HS



Manufacturer	EATON - MOELLER
MPN / Reference	Z-VPS-4/1p+HS
Catalog number	Y7-302375
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-C2C1F0397D
Generated	2026-08-05

Product Overview

Splint HK 1p+HK short pin
Eaton Distribution parts. Busbar AUX 1p+AUX short pin
Busbar AUX 1p+AUX short pin for special application

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 302375 Model Code Z-VPS-4/1p+HS EAN 9010238159334

Product Length/Depth 1000 mm Product Height 23.5 mm Product Width 4.5 mm Product Weight 0.088 kg Compliances

RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Pin Cross section 4 mm² Number of modular spacings 38 Number of phases 1
Pitch dimensions 13 mm Rated operating voltage (Ue) - max 1500 V Rated surge voltage 0 KV Rated uninterrupted current
(Iu) 32 A Rated short-time withstand current (Icw) 0 kA Number of poles Single-pole Color Grey Rated conditional
short-circuit current (Iq) 0 kA Suitable for 38 devices

ETIM for 302375 Low-voltage industrial controls and switchgear (EC000215)

Feature Name
Feature Value

Number of phases (EF000351)

1
Number of poles (EF001391)
1
Suitable for number of devices (EF007241)
38
Module width (EF007504)
13 mm
Cross section (EF000649)
4 mm²
Length (EF001438)
1000 mm
Can be cut to size (EF015250)
Yes
Width in number of modular spacings (EF002950)
38
Rated permanent current I_u (EF001389)
32 A
Type of electric connection (EF003961)
Pin
Insulated (EF000019)
Yes
Rated surge voltage (EF002993)
0 kV
Conditioned rated short-circuit current I_q (EF001444)
0 kA
Max. rated operation voltage U_e (EF007357)
1500 V
Rated short-time withstand current I_{cw} (EF007050)
0 kA
Suitable for devices with N-conductor (EF007218)
No
Suitable for devices with auxiliary switch (EF007217)
No
Colour (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-VPS-4/1p+HS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.