

INDUSTRIAL COMPONENT DATA

ZBT32-32 190942 Y7-190942 EATON ELECTRIC Overload relay, narrow 24 32 A 1 NO + 1 NC direct Mounting in DILMT..

Brand: EATON - MOELLER | Manufacturer Part Number: ZBT32-32



Manufacturer	EATON - MOELLER
MPN / Reference	ZBT32-32
Catalog number	Y7-190942
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-8DD373E4BB
Generated	2026-08-06

Product Overview

Overload relay, narrow; 24 - 32 A; 1 NO + 1 NC; direct Mounting in DILMT17...32

ZBT32-32

Overload relay, ZBT32, Ir= 24 - 32 A, 1 N/O, 1 N/C, Direct mounting, IP20

Overload relay, Product range: Overload relay ZBT up to 97 A, Accessories, Accessories: Overload relays, Frame size: ZBT32, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Direct mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILMT17, DILMT25, DILMT32, Standards: IEC/EN 60947, GB14048, Degree of Protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Thermal Relays
--------------	----------------------------------

Additional Product Information

Overload relay, ZBT32, Ir= 24 - 32 A, 1 N/O, 1 N/C, Direct mounting, IP20
Overload relay, Product range: Overload relay ZBT up to 97 A, Accessories, Accessories: Overload relays, Frame size: ZBT32, Phase-failure sensitivity: IEC/EN 60947, VDE 0660 Part 102, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Mounting type: Direct mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, For use with: DILMT17, DILMT25, DILMT32, Standards: IEC/EN 60947, GB14048, Degree of Protection: IP20
Delivery program
Product range
Overload relay ZBT up to 97 A
Product range
Accessories
Accessories
Overload relays
Frame size
ZBT32
Phase-failure sensitivity
IEC/EN 60947, VDE 0660 Part 102
Description
Test/off button
Reset pushbutton manual/auto

Trip-free release

Overload trigger: tripping class 10 A Mounting type Direct mounting [Ir] 24 - 32 A Contact sequence Auxiliary contacts N/O =

Normally open 1 N/ON/C = Normally closed 1 N/C For use with DILMT17

DILMT25

DILMT32 Technical data

General Standards IEC/EN 60947, GB14048 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Operating range to IEC/EN 60947: -5 - +40 °C Ambient

temperature Open-25 - +55 °C Ambient temperature Enclosed- 25 - 40 °C Temperature compensation Continuous Weight 0.114

kg Mechanical shock resistance 10

Sinusoidal

Shock duration 10 ms g Degree of Protection IP20 Protection against direct contact when actuated from front (EN 5027...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZBT32-32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.