

INDUSTRIAL COMPONENT DATA

MCI18086R5 ELDON Floor standing, 1800x800x600

Brand: ELDON | Manufacturer Part Number: MCI18086R5



Manufacturer	ELDON
MPN / Reference	MCI18086R5
Catalog number	18086
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-1C2744FA1C
Generated	2026-07-31

Product Overview

Floor standing, 1800x800x600

Self-supporting, 1800x800x600, combinable, 1 door, no MP, mild steel, IP55

Floor standing, combinable, 1800x800x600, 1-door, Mild steel, Zinc plated, IP55

Floor standing, 1800x800x600, Combinable enclosure, 1-door, no MP, mild steel, IP55

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ELDON > Steel Floor Standing Enclosures

Additional Product Information

Features

Material: Frame: 1.5 mm steel plate. Door: 2 mm steel plate. Roof plate: 1.5 mm steel plate. Bottom plates: 1 mm galvanized steel. 19" profiles: 2 mm zinc plated steel

Frame: Seam welded reversed open profiles with 25 mm hole pattern, according to DIN 43660. Including integrated external hole pattern

Rear door: Mounted with hinges, allowing left or right hand opening. Including door frame with 25 mm hole pattern

Side panels: Supplied as an accessory

Roof panel: Removable

Lock: Espagnolette 4-point locking system. Does not interfere with the enclosure inner space. Standard double-bit lock with 3 mm insert. Standard inserts, cylinders, lift handles and T-handles are available as accessories

Bottom plates: Consists of three or four (D>600) pieces

19" profiles: Provides front and side universal 19" hole pattern. Adjustable in depth by steps of 25 mm

Earthing: All panels are earthed through their fittings and are equipped with a separate earthing stud

Finish: Frame, rear door and roof plate: RAL 7035 structured powder coating. 19" profiles: zinc plated steel

Protection: Complies with IP 55 TYPE 12 IK 10, when plain front door and side panels are fitted

Mounting requirements: Add side panels for closed sides. Front frame can be covered with FFC or fitted with a glazed or plain door

Delivery: Frame with fitted rear door, roof panel, bottom plates. 19" profiles at front and fixing brackets CIB. For enclosures 2200 mm height, delivery includes two CMB profiles mounted in dep...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ELDON / MCI18086R5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.