

INDUSTRIAL COMPONENT DATA

MCS20055PER5 ELDON Floor standing, 2000x500x500 MCS20055PER5

Brand: ELDON | Manufacturer Part Number: MCS20055PER5



Manufacturer	ELDON
MPN / Reference	MCS20055PER5
Catalog number	20055
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-664D1C810C
Generated	2026-07-31

Product Overview

Floor standing, 2000x500x500 MCS20055PER5
Self-supporting, 2000x500x500, combinable, 1 door, no MP, mild steel, IP55
Modular Single Door, MCS without Plate, 2000x500x500mm, Light Gray, Mild Steel
Floor standing, 2000x500x500

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ELDON > Steel Floor Standing Enclosures

Additional Product Information

Features

Material: Frame: 1.5 mm painted steel. Door: 2 mm painted steel. Rear, roof and side panels: 1.5 mm painted steel.
Mounting plate: 3 mm galvanized steel. Bottom plates: 1 mm galvanized steel.
Frame: Seam welded reversed open profiles with 25 mm hole pattern, according to DIN 43660. Including integrated external hole pattern.
Door: Mounted with four hinges allowing left or right hand opening. Including door frame with 25 mm hole pattern.
Rear panel: Fitted by M6 torx screws. Standard facilities for rear door mounting. RD version comes with rear door instead of rear panel.
Side panels: Supplied as an accessory.
Roof panel: Removable.
Lock: Espagnolette 4-point locking system. Does not interfere with the enclosure inner space. Standard double-bit lock with 3 mm insert. Standard inserts, cylinders, lift handles and T-handles are available as accessories.

Bottom plates: Consists of three or four (D>600) pieces.

Mounting plate: Double folded and slides into position. Adjustable in depth by steps of 25 mm, with the MPD02 accessory.

Supplied, attached on the outside of the enclosure packaging.

Earthing: All panels are earthed through their fittings and are equipped with a separate earthing stud.

Finish: RAL 7035 structured powder coating.

Protection: Complies with IP 55 TYPE 12 IK 10.

Mounting requirements: Standard delivery ready for combined installation. For stand-alone installation add side panels.

Delivery: Frame with fitted door, rear panel, roof panel, bottom plates,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ELDON / MCS20055PER5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.