

INDUSTRIAL COMPONENT DATA

MCSE20086R5 ELDON Floor standing, 2000x800x600, Combinable enclosure, 1-door, with MP, mild steel, IP56

Brand: ELDON | Manufacturer Part Number: MCSE20086R5


ENERGY AND AUTOMATION
image not available

Manufacturer	ELDON
MPN / Reference	MCSE20086R5
Catalog number	20086
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-BDDC7846D1
Generated	2026-07-29

Product Overview

Floor standing, 2000x800x600, Combinable enclosure, 1-door, with MP, mild steel, IP56

Self-supporting, 2000x800x600, combinable, 1 door, with MP, mild steel, IP54

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ELDON > Steel Floor Standing Enclosures

Additional Product Information

Features

Material: Frame: 1.5 mm / 1.75 mm zinc plated steel. Door: 2 mm zinc plated steel. Rear, roof and side panels: 1.5 mm zinc plated steel. Mounting plate: 3 mm galvanized steel. Bottom plates: 1 mm galvanized steel.

Frame: Seam welded reversed open profiles with 25 mm hole pattern, according to DIN 43660. Including integrated external hole pattern.

Door: With 4 hinges allowing left or right hand opening. Including door frame with 25 mm hole pattern. Sealing is attained by a conductive polyurethane EMC gasket.

Rear panel: Fitted by M6 torx screws. Standard facilities for rear door mounting.

Side panels: Supplied as an accessory.

Roof panel: Removable.

Lock: Espagnolette 4-point locking system. Does not interfere with the enclosure inner space. Standard double-bit lock with 3 mm pin. Standard inserts, cylinders, lift handles and T-handles are available as accessories.

Mounting plate: Double folded and slides into position. Adjustable in depth by steps of 25 mm, with the MPD02 accessory.

In the enclosure delivery, mounting plate is supplied, attached on the outside of the enclosure packaging.

Bottom plates: Consists of three pieces. For 800 mm deep 4 pieces.

Earthing: All panels are earthed through their fittings and are equipped with a separate earthing stud.

Finish: RAL 7035 structure powder coating on the outside only.

Protection: IP 54 TYPE 12 IK 10.

Delivery: Frame with fitted door, rear panel, roof panel, bottom plates, mounting plate and door frame. Delivery also i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ELDON / MCSE20086R5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.