

INDUSTRIAL COMPONENT DATA

MCSS20108RD25 ELDON Self-supporting, 2000x1000x800, Combinable, 1 door, with MP, p. rear, ac. stainless steel..

Brand: ELDON | Manufacturer Part Number: MCSS20108RD25



ENERGY AND AUTOMATION

image not available

Manufacturer	ELDON
MPN / Reference	MCSS20108RD25
Catalog number	20108
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-2F565DB2DC
Generated	2026-07-28

Product Overview

Self-supporting, 2000x1000x800, Combinable, 1 door, with MP, p. rear, ac. stainless steel 316, IP66

Floor stand., 2000x1000x800, Combinable encl. 1-door with MP r-door SS 316, IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ELDON > Stainless steel enclosures

Additional Product Information

Features

Material: AISI 316L pre-grained stainless steel. Frame: 1.5 mm. Door: 2 or 2.5 mm. Rear, roof and bottom plate: 2 or 2.5 mm. Mounting plate: 3 mm galvanized steel.

Frame: Seam welded reversed open profiles with 25 mm hole pattern according to DIN 43660.

Door: Mounted with four hinges allowing left or right hand opening. Including door frame with 25 mm hole pattern.

Rear: Rear panel fitted by M6 tork screw. Rear door instead of rear panel. RD version comes with rear door instead of rear panel.

Side panels: Supplied as an accessory.

Roof panel: Removable.

Lock: Espagnolette locking system with lock catcher made in AISI 316L and additional locks in top and bottom for enclosures with W=1000 mm. Swing handle SS 316L with half cylinder keyed EK 333.

Bottom plates: One piece bottom plate with injected polyurethane gasket to ensure maximum sealing or two pieces for the rear door version.

Mounting plate: Double folded and slides into position. Adjustable in depth by steps of 25 mm with the MPD02 accessory.

Mounting plate is delivered attached on the outside of the enclosure packaging. For Enclosure with rear doors, two mounting plates mounted back to back with MPBB06.

Earthing: All panels are earthed through their fittings and are equipped with a separate earthing stud.

Finish: 240s pre-grained stainless steel (0,5 microns average).

Protection: Complies with IP 66 TYPE 4X, 12 IK 10. if are used with SPMSXXXXOG.

Approvals: CE, EAC, DNV-GL, GOST, Kema Keur, Lloyds shipping, cU...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ELDON / MCSS20108RD25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.