

INDUSTRIAL COMPONENT DATA

ADR1201240 ELDON Wall mounted, 1200x1200x400, Compact enclosure, 2-door, with MP, stainless 304, IP55

Brand: ELDON | Manufacturer Part Number: ADR1201240



Manufacturer	ELDON
MPN / Reference	ADR1201240
Catalog number	1201240
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-CC848CB61A
Generated	2026-08-01

Product Overview

Wall mounted, 1200x1200x400, Compact enclosure, 2-door, with MP, stainless 304, IP55

Mural, 1200x1200x400, compact, 2-door, with MP, stainless 304, IP55

Double Door Enclosure, ADR, 1200x1200x400mm, Brushed, Stainless 304

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ELDON > Stainless steel enclosures

Additional Product Information

Features

Material: AISI 304L / AISI 316L pre-grained stainless steel. Body: 1.5 mm. Door: 2 mm. Mounting plate: 2.5 mm galvanized steel.

Body: Folded and seam welded. For ease of installation, each back corner of the enclosure is laser-marked to precisely indicate where to drill holes and affix AWS wall mounting brackets.

Door: Corner formed in one piece. Surface mounted, with 130° opening. Concealed AISI 304 stainless steel hinges with captive pin. Sealing is ensured by an injected polyurethane gasket or by an injected silicone gasket. Inner M6 welded studs to mount optional door profiles MMDP.

Lock: nVent HOFFMAN customized zamak double-bit 3 mm lock, with 90° movement and anti-vibration mechanism.

Espagnolette three point locking. Stainless steel lock and other versions are available as accessories.

Mounting plate: The mounting plate is marked vertically at 10 mm intervals, for easy horizontal positioning of equipment. On the top and bottom there are holes to facilitate cable fixing. Fixed onto M8 press welded studs to the rear of the enclosure.

All sides, from 800 mm and above, are strengthened by folded edges. By using the AMG accessory, the mounting plate

position can be adjusted to any depth.

Cable access: No gland plate openings as standard, to maximise sealing and cleanliness.

Finish: 400 pre-grained stainless steel.

Protection: Corresponds with IP 55, TYPE 12, IK 10.

Delivery: Enclosure with door, mounting plate, metallic key and mounting accessories.

Additional in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ELDON / ADR1201240 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.