

## INDUSTRIAL COMPONENT DATA

# ASR0604021-316 ELDON Wall mounted, 600x400x210

## ASR0604021-316

Brand: ELDON | Manufacturer Part Number: ASR0604021-316



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | ELDON                                |
| MPN / Reference | ASR0604021-316                       |
| Catalog number  | 0604021                              |
| Category        | Enclosure/switchgear cabinet (empty) |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-866005AF3F                        |
| Generated       | 2026-08-03                           |

### Product Overview

Wall mounted, 600x400x210 ASR0604021-316  
Mural, 600x400x210, compact, 1-door, with MP, stainless steel 316, IP66  
Single Door Enclosure, ASR, 600x400x210mm, Brushed, Stainless 316

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path ELDON > Stainless steel enclosures

### Additional Product Information

#### Features

Material: AISI 304L / AISI 316L pre-grained stainless steel. Body: 1.5 mm. Door for AISI 304L: 1.5 mm / 2 mm. Door for AISI 316L: 2 mm. Mounting plate: 2 mm galvanized steel.

Body: Folded and seam welded. For ease of installation, each back corner of the enclosure is laser-marked to precisely indicate where to drill holes and affix AWS wall mounting brackets.

Door: Corner formed in one piece. Surface mounted, with 130° opening. Concealed AISI 304 stainless steel hinges with captive pin. Can be mounted to allow left or right hand opening. Sealing is ensured by an injected polyurethane gasket or by an injected silicone gasket. Inner M6 welded studs, to mount optional door profiles MMDP.

Lock: nVent HOFFMAN customized zamak double-bit 3 mm lock, with 90° movement and anti-vibration mechanism. Two locks for 600 mm high to 800 mm high enclosures. Espagnolette three point locking or 3 locks for 1000 mm high enclosures and above. Stainless steel lock and other versions are available as accessories.

Mounting plate: The mounting plate is marked vertically at 10 mm intervals, for easy horizontal positioning of equipment. On the top and bottom there are holes to facilitate cable fixing. Fixed onto M8 press welded studs to the rear of the enclosure.

All sides, from 800 mm and above, are strengthened by folded edges. By using the AMG accessory, the mounting plate position can be adjusted to any depth.

Cable access: No gland plate openings as standard, to maximise sealing and cle...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ELDON / ASR0604021-316 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.