

INDUSTRIAL COMPONENT DATA

1SNA115265R2400 ENTRELEC MS4/6 Screw Clamp Terminal Blocks Miniblocks Grey

Brand: ENTRELEC | Manufacturer Part Number: 1SNA115265R2400



Manufacturer	ENTRELEC
MPN / Reference	1SNA115265R2400
Catalog number	1SNA115265R2400
Category	Passive connection
Minimum order	100 units
Document ID	EO-89AF1AFEE9
Generated	2026-08-06

Product Overview

1SNA115265R2400 ENTRELEC MS4/6 Screw Clamp Terminal Blocks Miniblocks Grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ENTRELEC > Passive connection > SNA Clamp various terminal blocks

Additional Product Information

- Save space with compact over-all dimensions terminal block. - Flexibility: snap onto symmetrical and asymmetrical rails.

Ordering

Minimum Order Quantity:100 piece

Customs Tariff Number:85369010

Color:Grey

Dimensions

Product Net Height: 41mm

Product Net Depth: 31mm

Product Net Weight: 6g

Product Net Width: 6mm

Technical

Spacing:6 mm

Connection Type:Screw clamp

Function:Miniblock

Number of Levels:1

Connecting Capacity-Main Circuit:Screw Clamp / Flexible 1x 0.22 ... 4 mm²
Screw Clamp / Rigid 1x 0.2 ... 4 mm²
Gauge Type:A4
Rated Current (In):Main Circuit 32 A
Rated Short-time Withstand Current (Icw):for 1 s 480 A
Rated Voltage (Ur):630 V
Rated Impulse Withstand Voltage (Uimp):4000 V
Dielectric Test Voltage:2500 V
Pollution Degree:3
Degree of Protection:acc. to IEC 60529. IEC 60947-1. EN 60529 Main Terminals IP20
Insulation Material:Polyamide
Mounting on DIN Rail:G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715
TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:10.0 mm
Recommended Screw Driver:4 mm
Tightening Torque:acc. IEC 60947-1 0.5 N·m
Manufacturer 0.8 N·m
Rated Cross-Section:4 mm²
Technical UL/CSA
Connecting Capacity Main Circuit UL/CSA:Screw Clamp / Rigid 1x 22 ... 10 AWG
Connecting Capacity UL/CSA:Screw Clamp / Rigid 22 ... 10 AWG
Stranded 10 AWG
Flammability According to UL94:V0
Maximum Operating Voltage UL/CSA:Main Circuit 600 V
Environmental
RoHS Status:Following EU Directive 2002/95/EC Au...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ENTRELEC / 1SNA115265R2400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.