

INDUSTRIAL COMPONENT DATA

146723 IME ALIM DECOUP MOD 24V 60W

Brand: IME | Manufacturer Part Number: 146723



Manufacturer	IME
MPN / Reference	146723
Catalog number	146723
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-F6AE202B29
Generated	2026-07-31

Product Overview

ALIM DECOUP MOD 24V - 60W

Single-phase switched modular power supply, input 100 - 240Vac - output 24Vdc - 2.5A

Single-phase switched modular power supply, 100 - 240Vac - 24Vdc

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

Single-phase - 15 to 92 W - No-load consumption less than 0.3W -Adjustable output voltage Input voltage: 100 to 240V~

Output voltage: 24V= - Nominal power: 36W - Nominal intensity: 1.5A - Output range (V): 21.6 to 29 - 2 modules 17.5

mm.Type of supply voltage AC/DC

1st output voltage (Min-Max) 21.6-29 V

Maximum Output Current 1 2.5 A

Adjustable output voltage Yes

Nominal value output voltage 1 24 V

Output Current Rating 1 2.5 A

Short Circuit Protection Yes

Rated AC supply voltage at 50 Hz (Min-Max) 100-240 V

Regulated output voltage Yes

Power Supplied 60 W

Stabilized Yes

Running the electrical connection Threaded connection

Rail mounting possible Yes
Suitable for wall mounting No
Suitable for series installation Yes
Width in number of modular spaces 3
Direct mounting possible No
Width 52.5 mm
Height 90 mm
Depth 54.5 mm
Suitable for safety functions Yes
Operating Temperature (Min-Max) -30-45 °C
Frequency (Min-Max) 50-60 Hz
Direction of the electricity supply From the bottom
Display of markings on the connection terminals Yes
Terminal Capacity (Min-Max) 2.5-2.5 mm²
Label Space/Print Area No
ETIM for 146723 Low-voltage industrial controls and switchgear (EC002540)
Feature Name
Feature Value
Power output (EF003034)
60 W
Height (EF000040)
90 mm
Wall mounting possible (EF003973)
No
Suitable for safety functions (EF001597)
Yes
Suitable for rail mounting (EF003972)
Yes
Output voltage stabilized (EF003092)
Yes
Rated supply voltage AC 50 Hz (EF007076)
100 V
Short-circuit-proof (EF0073...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 146723 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.