

INDUSTRIAL COMPONENT DATA

406457 IME DX3 IS 3P 20A SWITCH

Brand: IME | Manufacturer Part Number: 406457



Manufacturer	IME
MPN / Reference	406457
Catalog number	406457
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-2918BA1D96
Generated	2026-07-29

Product Overview

DX3 IS 3P 20A SWITCH

DX³ -IS - 3P - 400V~ - 20A - 2 modules disconnect switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

DX3 IS 3 pole switch 20A. Disconnecter switches - Use category AC 22A according to EN 60947-3 - gray handle - Double cut contacts - Accepts a signaling aid DX³ (AC) Tripolar 400V~ - Nominal current: 20A - Number of modules: 2.

Disconnecting switches DX³ -IS - sectioning in installation header, 16 to 125A - Mounting in symmetrical profile EN 60715 - Fully visible cut. Running as a main switch Yes

Operation as a maintenance/repair switch No

Operation as a safety switch Yes

Execution as an emergency stop device No

Maximum Rated Operating Voltage Ue AC 400 V

Permanent nominal current Iu 20 A

Conditional Short-Circuit Current Rating Iq 4500 kA

Number of poles 3

Optional motorized drive No

Integrated motorized drive No

Device construction Fixed integrated technology for integrated device

Floor Mount No

Suitable for 4-hole front mounting No
Suitable for center front mounting No
Suitable for distributor installation Yes
Suitable for intermediate mounting No
Execution of the actuator element Handle
Interlockable Yes
Main Current Circuit Connection Type Threaded connection
Degree of protection (IP), front IP20
Width 35.6 mm
Height 94.8 mm
Depth 76.4 mm
Impact resistance IK04
Operating Temperature (Min-Max) -25-70 °C
Storage Temperature (Min-Max) -40-70 °C
Type of voltage AC
Direction of the electricity supply From the top or bottom
Display of markings on the connection terminals No
Colour Grey
RAL number 7035
Halogen-free Yes
Terminal Capacity (Min-Max) 1.5-16 mm²
Connection type Busba...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 406457 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.