

INDUSTRIAL COMPONENT DATA

406547 IME DX3 IS-A 4P 125A SWITCH

Brand: IME | Manufacturer Part Number: 406547



Manufacturer	IME
MPN / Reference	406547
Catalog number	406547
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-62C5FE32D6
Generated	2026-07-29

Product Overview

DX3 IS-A 4P 125A SWITCH

DX³ -IS disconnect switch - with remote trip - 4P - 125A - 6mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

ETIM for 406547 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as safety switch (EF006985)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Number of auxiliary contacts as normally open contact (EF001376)

0

Max. rated operation voltage Ue AC (EF007355)

415 V

Version as main switch (EF006981)

Yes

Number of auxiliary contacts as change-over contact (EF003531)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Interlockable (EF006281)

Yes

Rated short-time withstand current I_{cw} (EF007050)

1 kA

Voltage release optional (EF007491)

Yes

Device construction (EF008240)

Complete device in housing

Number of poles (EF001391)

4

Type of electrical connection of main circuit (EF006819)

Screw connection

Version as emergency stop installation (EF006959)

Yes

Motor drive integrated (EF006697)

No

Version as reversing switch (EF009408)

No

Type of control element (EF006976)

Toggle

Rated operation power at AC-23, 400 V (EF007027)

40 kW

Rated permanent current I_u (EF001389)

125 A

Suitable for front mounting 4-hole (EF007247)

Yes

Suitable for front mounting centre (EF007248)

No

Suitable for intermediate mounting (EF007264)

No

Motor drive optional (EF007386)

Yes

Colour control element (EF007167)

Red

Rated permanent current at AC-21, 400 V (EF009165)

125 A

Suitable for distribution board installation (EF007262)

Yes

Rated operating voltage (EF001435)

48 V

Degree of protection (IP), front side (EF003118)

IP20

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 406547 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.