

## INDUSTRIAL COMPONENT DATA

## 412410 IME TELERRUPTOR 16A 2NA BOB. 24V

Brand: IME | Manufacturer Part Number: 412410



|                 |                |
|-----------------|----------------|
| Manufacturer    | IME            |
| MPN / Reference | 412410         |
| Catalog number  | 412410         |
| Category        | Latching relay |
| Minimum order   | 1 Pcs          |
| Document ID     | EO-2D2EF19CB6  |
| Generated       | 2026-07-27     |

## Product Overview

TELERRUPTOR 16A 2NA BOB. 24V

Standard relay 24V~ - 2P - 250V~ - 16A - 2NA - 1 module

Standard Remote Switch 24V~ - 2P - 250V~ - 16A - 2NA - 1mod

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |     |
|--------------|-----|
| Catalog path | IME |
|--------------|-----|

## Additional Product Information

Telerruptor 16A 2NA coil 24V. Standard switches - The auxiliaries and the compensator can be associated with standard Bipolar teleswitches 16A - 250V~ - Control current voltage: 24V~ - Contact type: 2 NC - Number of modules: 1. CX<sup>3</sup> teleswitches - Comply with EN 60669-2-2 standard.function Mechanical for centralized control

Type of mounting DIN Lane

Width in number of modular spaces 1

Installation Depth 44 mm

Number of contacts normally opened 2

Number of Normally Closed Contacts 0

Number of investor contacts 0

Control voltage 1 (Min-Max) 22-26 V

Control voltage type 1 AC

Control voltage frequency 1 (Min-Max) 50-60 Hz

Width 17.8 mm

Height 95 mm

Depth 70.2 mm

ETIM for 412410 Modular devices for distribution board/surface mounting (EC000188)

Feature Name

Feature Value

Function (EF000030)

Mechanical for centralized control

Number of contacts as change-over contact (EF008257)

0

Width in number of modular spacings (EF002950)

1

Mounting method (EF000003)

DIN rail

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as normally open contact (EF008256)

2

Type of control voltage 1 (EF002954)

AC

Control voltage 1 (EF002952)

22 V

Built-in depth (EF000218)

44 mm

Frequency control voltage 1 (EF002956)

50 Hz

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412410 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.