

INDUSTRIAL COMPONENT DATA

412430 IME CONTACT AUXILIARY 2 MOD 25A

Brand: IME | Manufacturer Part Number: 412430



Manufacturer	IME
MPN / Reference	412430
Catalog number	412430
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-44D9328AE6
Generated	2026-07-31

Product Overview

CONTACT AUXILIARY 2 MOD

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path IME

Additional Product Information

Auxiliary contact 2 modules 25A. Signaling auxiliaries - Inverter auxiliary contacts - Allow standard signaling of the position status of the contacts of the product to which they are associated - For contactors 2 modules 25A - 2 Auxiliaries maximum - Mounted to the left of the contactor - Max I: 5A - Voltage: 250V~ - 50/60 Hz - Contact: NC + NO - Number of modules: 0.5.

Auxiliaries and connection module for CX³ contactors. Equipment Installation Auxiliary switch/relay

function Signal switch

Width in number of modular spaces 0.5

Number of contacts normally opened 1

Number of Normally Closed Contacts 1

Number of investor contacts 0

Number of error signal switches 0

Nominal switching current 5 A

Nominal voltage 250 V

Type of voltage AC

Self-tested for residual current function No

Suitable for max.. No. of Poles of Main Contact Unit (Total) 4

Suitable for max.. Main Contact Unit Amperage 25 A

Width 9 mm

Height 84.5 mm

Depth 67 mm

ETIM for 412430 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Function (EF000030)

Signalling switch

Number of fault-signal switches (EF007613)

0

Number of contacts as change-over contact (EF008257)

0

Width in number of modular spacings (EF002950)

0.5

Suitable for max. current main contact unit (EF008730)

25 A

Voltage type (EF000187)

AC

Number of contacts as normally closed contact (EF008255)

1

Number of contacts as normally open contact (EF008256)

1

Rated switch current (EF006706)

5 A

With auto test for ea...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412430 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.