

**INDUSTRIAL COMPONENT DATA**

# 412431 IME CONTACT AUX. P/CONT 40A and 63A

Brand: IME | Manufacturer Part Number: 412431



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | IME                                             |
| MPN / Reference | 412431                                          |
| Catalog number  | 412431                                          |
| Category        | Auxiliary device for distribution board devices |
| Minimum order   | 1 Pcs                                           |
| Document ID     | EO-A9919F5147                                   |
| Generated       | 2026-08-03                                      |

## Product Overview

CONTACT AUX. P/CONT 40A and 63A

Auxiliary for 40 and 63A contactors - aux inverter contact - 250V~/5A - NC+NA

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |     |
|--------------|-----|
| Catalog path | IME |
|--------------|-----|

## Additional Product Information

Auxiliary contact for Contactor 40/63A. Signaling auxiliaries - Auxiliary inverter contacts - Allow standard signaling of the position status of the contacts of the product to which they are associated - For 40 and 63A contactors - Mounted to the left of the contactor - 1 maximum auxiliary - Max I: 5A - Voltage: 250V~ - 50/60 Hz - Contact: NC + NO - Number of modules: 0.5. Auxiliaries and connection module for CX<sup>3</sup> contactors. Equipment Installation Auxiliary switch/relay

function Signal switch

Width in number of modular spaces 0.5

Number of contacts normally opened 1

Number of Normally Closed Contacts 1

Number of investor contacts 0

Number of error signal switches 0

Nominal switching current 5 A

Nominal voltage 250 V

Type of voltage AC

Self-tested for residual current function No

Suitable for max.. No. of Poles of Main Contact Unit (Total) 4

Suitable for max.. Main Contact Unit Amperage 63 A

Width 9 mm

Height 83 mm

Depth 66 mm

ETIM for 412431 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Function (EF000030)

Signalling switch

Number of fault-signal switches (EF007613)

0

Number of contacts as change-over contact (EF008257)

0

Width in number of modular spacings (EF002950)

0.5

Suitable for max. current main contact unit (EF008730)

63 A

Voltage type (EF000187)

AC

Number of contacts as normally closed contact (EF008255)

1

Number of contacts as normally open contact (EF008256)

1

Rated switch current (EF006706)

5 A

With auto test for ea...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412431 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.