

INDUSTRIAL COMPONENT DATA

412502 IME CONTACTOR 25A 3NA 230V

Brand: IME | Manufacturer Part Number: 412502



Manufacturer	IME
MPN / Reference	412502
Catalog number	412502
Category	Installation contactor for distribution board
Minimum order	4 Pcs
Document ID	EO-3024CF60E3
Generated	2026-08-01

Product Overview

CONTACTOR 25A 3NA 230V

Silent contactor - 230V~ - 3P - 400V~/25A - 3 NA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	IME
--------------	-----

Additional Product Information

Contactors 25A 3NA 230V. Silent contactors with forced switch - Coil 230V~ - Forced running contactors with automatic return Tripolar 400V~ - Max I: 25A - Contact type: 3 NA - Number of modules: 2. CX³ contactors - with manual control - Comply with EN 61095 standard - Suitable for feeding comb passage up to 25A - Mounting on symmetrical profile. Rated Operating Voltage (Min-Max) 400-400 V
Rated Operating Current 25 A
Control voltage rating (Min-Max) 195-253 V
Operating voltage type AC
Voltage Type (Excitation Voltage) AC
Number of contacts normally opened 3
Number of Normally Closed Contacts 0
Maximum incandescent lamp load 3000 W
Maximum fluorescent lamp load 2100 VA
Maximum fluorescent lamp load (duo circuit) 2200 VA
Maximum fluorescent lamp load (parallel-compensated) 1000 VA
Slider for manual operation Yes

Width in number of modular spaces 2
Installation Depth 44 mm
Additional equipment possible Yes
Protection Class (IP) IP2X
Width 35.6 mm
Height 94.9 mm
Depth 72.6 mm
ETIM for 412502 Modular devices for distribution board/surface mounting (EC001653)
Feature Name
Feature Value
Max. load fluorescent lamp (EF004971)
2100 VA
Rated operation current (EF007679)
25 A
Degree of protection (IP) (EF005474)
IP2X
Width in number of modular spacings (EF002950)
2
Max. incandescent lamp load (EF004952)
3000 W
Additional equipment possible (EF008148)
Yes
Max. load fluorescent lamp (parallel compensated) (EF004973)
1000 VA
Max. load fluorescent lamp (Duo circuit) (EF004972)
2200 VA
Voltage...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send IME / 412502 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.